

**METHODS OF PROVIDING DATA SERVICES OVER DATA NETWORKS  
AND RELATED DATA NETWORKS, DATA SERVICE PROVIDERS,  
ROUTING GATEWAYS AND COMPUTER PROGRAM PRODUCTS**

Inventors:

Maria Adamczyk

Jeffery Patrick Cassanova

Sammie Walter Hill

Li Zhang

Scott C. Hatfield

Myers Bigel Sibley & Sajovec, P.A.

Suite 600, 4140 Parklake Ave

Raleigh, NC 27612

Mailing Address:

P.O. Box 37428

Raleigh, NC 27627

919-854-1400

Attorney Reference No. 9400-50

BellSouth Reference No. 030315

**DRAFT**

**Contains private and/or proprietary information  
ATTORNEY/CLIENT PRIVILEGED**

**METHODS OF PROVIDING DATA SERVICES OVER DATA NETWORKS  
AND RELATED DATA NETWORKS, DATA SERVICE PROVIDERS,  
ROUTING GATEWAYS AND COMPUTER PROGRAM PRODUCTS**

**RELATED APPLICATION**

This application claims the benefit of and priority to U. S. Provisional Patent Application No. 60/470,650, filed May 15, 2003, the disclosure of which is hereby incorporated herein by reference as if set forth in its entirety.

5

**FIELD OF THE INVENTION**

The present invention relates to communication networks, and, more particularly, to managing Quality of Service (QoS) in communication networks.

10

**BACKGROUND OF THE INVENTION**

The Internet is a decentralized network of computers that can communicate with one another via the internet protocol (IP). Although the Internet has its origins in a network created by the Advanced Research Project Agency (ARPA) in the 1960's, it has only recently become a worldwide communication medium. To a large extent, the explosive growth in use and traffic over the Internet is due to the development in the early 1990's of the worldwide Web (WWW), which is one of several service facilities provided on the Internet. Other facilities include a variety of communication services such as electronic mail, telnet, usenet newsgroups, internet relay chat (IRC), a variety of information search services such as WAIS and Archie, and a variety of information retrieval services such as FTP (file transfer protocol) and Gopher.

20

The WWW is a client-server based facility that includes a number of servers (computers connected to the Internet) on which Web pages or files reside, as well as clients (Web browsers), which interface the users with the Web pages. Specifically, Web browsers and software applications send a request over the WWW to a server requesting a Web page identified by a Uniform Resource Locator (URL) which notes both the server where the Web page resides and the file or files on that server which

25

5 make up the Web page. The server then sends a copy of the requested file(s) to the Web browser, which in turn displays the Web page to the user.

The topology of the WWW can be described as a network of networks, with providers of network service called Network Service Providers, or NSPs. Servers that provide application-layer services as previously described may be described as  
10 Application Service Providers (ASPs). Sometimes a single service provider does both functions within a single business

In recent years, broadband access technologies, such as digital subscriber line (DSL), cable modems, asynchronous transfer mode (ATM), and frame relay have facilitated the communication of voice, video, and data over the Internet and other  
15 public and private networks. Because broadband technologies are typically deployed by a single transport service provider, like a Regional Bell Operating Company (RBOC), their Regional and Access Networks (RAN) are often shared by many NSPs and ASPs offering services that range from Internet access and VPN access to Voice over IP, Video on Demand, and Gaming. Up until recently, a given Customer  
20 Premises Network (CPN) would have been connected to a single service provider in a generic way, however a new standard for RAN service (DSL Forum TR-059) provides a RAN architecture that allows simultaneous access to multiple NSPs and ASPs and for differentiating the data transport service provided by a RAN to these service providers.

25 Moreover, broadband access technology has allowed service providers to expand their content and service offerings to both business and home users. For example, a user may subscribe to multiple services or applications, such as voice service, Internet access service, a video service, a gaming service, *etc.* from one or more service providers. These services and/or applications may be delivered over a  
30 single network connection, such as a DSL line. Unfortunately, with multiple new connectivity options and applications that require specific characteristics from the network, there is also a need to establish priorities and bandwidth allocation among multiple services and/or applications so as to customize the content delivery according to the users' and/or providers' preferences.

35

## SUMMARY OF THE INVENTION

According to embodiments of the present invention, methods may be provided for operating a data network between a routing gateway for a subscriber and a data

5 service provider providing a data service. More particularly, methods may include  
receiving from the data service provider an identification of the routing gateway, an  
identification of the data service provider, and data flow characteristics of the data  
service for a session of the routing gateway using the data service provided by the  
data service provider. Responsive to receiving the identification of the routing  
10 gateway, the identification of the data service provider, and the data flow  
characteristics for the data service, the data flow characteristics of the data service for  
the routing gateway may be saved at the data network and forwarded to the routing  
gateway.

More particularly, the routing gateway may be coupled to the data network via  
15 a digital subscriber line and the identification of the routing gateway may be a digital  
subscriber line identification. In addition, the data flow characteristics of the data  
service may include a bandwidth characterization for the data service and a priority  
characterization for the data service. Moreover, an authorization code may be  
received for the data service, and the authorization code may be validated before  
20 saving the data flow characteristics.

Saving the data flow characteristics at the data network may include creating  
an application flow control record for the routing gateway, and the data flow  
characteristics may be saved at first and second databases within the data network.  
More particularly, the first database may be associated with a concentrator and the  
25 second database may be associated with a service manager.

Before receiving the data flow characteristics, a request may be received from  
the routing gateway for a session using the data service provided by the data service  
provider, and the request from the routing gateway may be forwarded to the data  
service provider. In addition, an interconnection may be provided between the  
30 routing gateway and the data service provider in accordance with the data flow  
characteristics to thereby support a session of the routing gateway using the data  
service provided by the data service provider.

Once the session is over, the data flow characteristics saved at the data  
network for the session of the routing gateway using the data service may be deleted,  
35 and the interconnection may be terminated between the routing gateway and the data  
service provider to thereby terminate the session of the routing gateway using the data  
service. In addition, a request may be received from the data service provider to  
delete the data flow characteristics for the session of the routing gateway using the



- 5 data service, wherein the data flow characteristics are deleted responsive to receiving the request before deleting the data flow characteristics.

According to additional embodiments of the present invention, methods may be provided for operating a data service provider providing a data service over a data network to a routing gateway for a subscriber using the data service. More  
10 particularly, methods may include transmitting to the data network an identification of the routing gateway, an identification of the data service provider, and data flow characteristics of the data service for a session with the routing gateway using the data service. The data service may be provided over the data network and routing gateway in accordance with the data flow characteristics transmitted to the data network to  
15 support a data session of the data service provider with the routing gateway.

Moreover, the routing gateway may be coupled to the data network via a digital subscriber line, and the identification of the routing gateway may be a digital subscriber line identification. In addition, the data flow characteristics of the data service may include a bandwidth characterization for the data service and a priority  
20 characterization for the data service.

An authorization code for the data service may be transmitted to the data service provider, and a validation of the authorization code may be received from the data network before providing the data service. Moreover, a request may be received from the routing gateway for a session using the data service before transmitting the  
25 identification of the routing gateway, the identification of the data service provider, and the data flow characteristics.

In addition, a request may be transmitted to the data service provider to delete the data flow characteristics for the session of the routing gateway using the data service. After transmitting the request to delete the data flow characteristics, the data  
30 service may be terminated over the data network and routing gateway.

According to yet additional embodiments of the present invention, methods may be provided for operating a routing gateway providing subscriber use of a data service provided by a data service provider over a data network. The methods may include receiving data flow characteristics of the data service for a session of the  
35 routing gateway using the data service provided by the data service provider. Access to the data service may be provided over the data network in accordance with the data flow characteristics received from the data network to support a data session with the data service provider.

5           More particularly, the routing gateway may be coupled to the data network via a digital subscriber line. Moreover, the data flow characteristics of the data service may include a bandwidth characterization for the data service and a priority characterization for the data service. In addition, a request may be transmitted to the data service provider for a session using the data service provided by the data service  
10 provider before receiving the data flow characteristics.

          According to still additional embodiments of the present invention, a data network may provide a data connection between a routing gateway for a subscriber and a data service provider providing a data service. The data network may include a first transceiver configured to receive from the data service provider an identification  
15 of the routing gateway, an identification of the data service provider, and data flow characteristics of the data service for a session of the routing gateway using the data service provided by the data service provider. A memory may be configured to save the data flow characteristics of the data service for the routing gateway at the data network responsive to receiving the identification of the routing gateway, the  
20 identification of the data service provider, and the data flow characteristics for the data service. A second transceiver may be configured to forward the data flow characteristics of the data service to the routing gateway.

          According to more embodiments of the present invention, a data service provider may provide a data service over a data network to a routing gateway for a  
25 subscriber using the data service. The data service provider may include a transceiver configured to transmit to the data network an identification of the routing gateway, an identification of the data service provider, and data flow characteristics of the data service for a session with the routing gateway using the data service. The transceiver may be further configured to provide the data service over the data network and  
30 routing gateway in accordance with the data flow characteristics transmitted to the data network to support a data session of the data service provider with the routing gateway.

          According to yet more embodiments of the present invention, a routing gateway may provide subscriber use of a data service provided by a data service  
35 provider over a data network. In particular, the routing gateway may include a transceiver configured to receive data flow characteristics of the data service for a session of the routing gateway using the data service provided by the data service provider. The transceiver may be further configured to provide access to the data

- 5 service over the data network in accordance with the data flow characteristics received from the data network to support a data session with the data service provider.

According to still more embodiments of the present invention, a computer program product may be configured to operate a data network between a routing gateway for a subscriber and a data service provider providing a data service. The computer program product may include a computer useable storage medium having computer-readable program code embodied in the medium. More particularly, the computer-readable program code may include computer-readable program code that is configured to receive from the data service provider an identification of the routing gateway, an identification of the data service provider, and data flow characteristics of the data service for a session of the routing gateway using the data service provided by the data service provider. The computer-readable program code may also include computer-readable program code that is configured to save the data flow characteristics of the data service for the routing gateway at the data network responsive to receiving the identification of the routing gateway, the identification of the data service provider, and the data flow characteristics for the data service. In addition, the computer-readable program code may include computer-readable program code that is configured to forward the data flow characteristics of the data service to the routing gateway.

25 According to additional embodiments of the present invention a computer program product may be configured to operating a data service provider providing a data service over a data network to a routing gateway for a subscriber using the data service. The computer program product may include a computer useable storage medium having computer-readable program code embodied in the medium. The computer-readable program code may include computer-readable program code that is configured to transmit to the data network an identification of the routing gateway, an identification of the data service provider, and data flow characteristics of the data service for a session with the routing gateway using the data service. The computer-readable program code may also include computer-readable program code that is configured to provide the data service over the data network and routing gateway in accordance with the data flow characteristics transmitted to the data network to support a data session of the data service provider with the routing gateway.

5           According to more embodiments of the present invention, a computer program product may be configured to operate a routing gateway providing subscriber use of a data service provided by a data service provider over a data network. The computer program product may include a computer useable storage medium having computer-readable program code embodied in the medium. The computer-readable program  
10   code may include computer-readable program code that is configured to receive data flow characteristics of the data service for a session of the routing gateway using the data service provided by the data service provider. The computer-readable program code may also include computer-readable program code that is configured to provide access to the data service over the data network in accordance with the data flow  
15   characteristics received from the data network to support a data session with the data service provider.

          Other systems, methods, and/or computer program products according to embodiments of the present invention will be or become apparent to one with skill in the art upon review of the following drawings and detailed description. It is intended  
20   that all such additional systems, methods, and/or computer program products be included within this description, be within the scope of the present invention, and be protected by the accompanying claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS

25           Other features of the present invention will be more readily understood from the following detailed description of specific embodiments thereof when read in conjunction with the accompanying drawings, in which:

**FIG. 1** is a block diagram that illustrates a conventional digital subscriber line (DSL) network;

30           **FIG. 2** is a block diagram that illustrates communication between end users and an application service provider (ASP) and a network service provider (NSP) via a regional/access network;

**FIG. 3** is a block diagram that illustrates the regional/access network;

**FIG. 4** is a block diagram that illustrates a broadband remote access server  
35   (BRAS) and a routing gateway (RG) in a network;

**FIG. 5** is a block diagram that illustrates access session types in the network of **FIG. 4** in accordance with some embodiments of the present invention;

5           **FIG. 6** is a block diagram that illustrates traffic classification and queuing treatments in accordance with some embodiments of the present invention;

**FIG. 7** illustrates business model options for using bandwidth on a communication medium in accordance with some embodiments of the present invention;

10           **FIG. 8** is a block diagram that illustrates relationships between a subscriber, the RG, the regional/access network, an ASP, and an NSP;

**FIGS. 9 - 12** are block diagrams that illustrates a data architecture (model) for managing quality of service (QoS) in a network in accordance with some embodiments of the present invention;

15           **FIG. 13** is a block diagram that illustrates an application framework infrastructure for managing QoS in a network in accordance with some embodiments of the present invention;

**FIG. 14** illustrates a messaging flow for a service provider authentication scenario using the application framework infrastructure of **FIG. 13** in accordance with  
20 some embodiments of the present invention;

**FIG. 15** illustrates a messaging flow for an application level bandwidth and QoS query scenario using the application framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

**FIG. 16** illustrates a messaging flow for an application level bandwidth and  
25 QoS modification scenario using the application framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

**FIG. 17** illustrates a messaging flow for an application flow control record creation scenario using the application framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

30           **FIG. 18** illustrates a messaging flow for an application flow control record deletion scenario using the application framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

**FIG. 19** illustrates a messaging flow for a NSP Point-to-Point Protocol (PPP) session level bandwidth and QoS modification scenario using the application  
35 framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

5           **FIG. 20** illustrates a messaging flow for a ASP/NSP PPP session level bandwidth and QoS query scenario using the application framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

**FIG. 21** is a block diagram that illustrates a turbo button architecture using the application framework infrastructure of **FIG. 13** in accordance with some  
10   embodiments of the present invention;

**FIG. 22** is an event diagram that illustrates operations of the turbo button architecture of **FIG. 21** in accordance with some embodiments of the present invention;

**FIG. 23** is a block diagram that illustrates a video conferencing architecture  
15   using the application framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

**FIGS. 24 and 25** are event diagrams that illustrate operations of the video conferencing architecture of **FIG. 23** in accordance with some embodiments of the present invention;

20           **FIG. 26** is a block diagram that illustrates traffic classification and queuing treatments for the video conferencing service in accordance with some embodiments of the present invention;

**FIG. 27** is a block diagram that illustrates operations of a video conferencing architecture in accordance with some embodiments of the present invention;

25           **FIG. 28** is a diagram that illustrates network topologies for supporting gaming applications in accordance with some embodiments of the present invention;

**FIG. 29** is a block diagram that illustrates a gaming architecture using the application framework infrastructure of **FIG. 13** in accordance with some embodiments of the present invention;

30           **FIG. 30** is a block diagram that illustrates traffic classification and queuing treatments for the gaming service in accordance with some embodiments of the present invention;

**FIG. 31** is an event diagram that illustrates operations of the gaming architecture of **FIG. 29** in accordance with some embodiments of the present  
35   invention; and

**FIG. 32** is a block diagram of network service providers in accordance with some embodiments of the present invention.

5           **FIGS. 33-35** are flow charts illustrating operations of data networks, application service providers, and routing gateways according to embodiments of the present invention.

### DETAILED DESCRIPTION OF EMBODIMENTS

10           While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit the invention to the particular forms disclosed, but on the contrary, the invention is to cover all modifications, equivalents, and alternatives falling within  
15 the spirit and scope of the invention as defined by the claims. Like reference numbers signify like elements throughout the description of the figures.

          The present invention may be embodied as systems, methods, and/or computer program products. Accordingly, the present invention may be embodied in hardware and/or in software (including firmware, resident software, micro-code, *etc.*).

20           Furthermore, the present invention may take the form of a computer program product on a computer-usable or computer-readable storage medium having computer-usable or computer-readable program code embodied in the medium for use by or in connection with an instruction execution system. In the context of this document, a computer-usable or computer-readable medium may be any medium that can contain,  
25 store, communicate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

          The computer-usable or computer-readable medium may be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, device, or propagation medium. More specific  
30 examples (a nonexhaustive list) of the computer-readable medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an optical fiber, and a portable compact disc read-only memory (CD-ROM). Note that the computer-usable  
35 or computer-readable medium could even be paper or another suitable medium upon which the program is printed, as the program can be electronically captured, via, for instance, optical scanning of the paper or other medium, then compiled, interpreted, or

5 otherwise processed in a suitable manner, if necessary, and then stored in a computer memory.

Embodiments of the present invention are described herein in the context of digital subscriber line (DSL) technology for purposes of illustration. It will be understood that the present invention is not limited to DSL technology. Indeed, other  
10 communication technologies and/or network configurations, such as, but not limited to, asynchronous transfer mode (ATM), frame relay, hybrid fiber coax (HFC), wireless broadband, and/or Ethernet may also be used in other embodiments of the present invention. In general, the present invention is not limited to any communication technology and/or network configuration, but is intended to  
15 encompass any technology and/or network configuration capable of carrying out operations described herein. Embodiments of the present invention are also described herein in the context of managing quality of service (QoS). As used herein, QoS includes, but is not limited to, treatment applied to an access session, application flow, and/or packet with respect to scheduling a resource, bandwidth allocation, and/or  
20 delivery target in an individual element or across an end-to-end system.

The detailed description of embodiments of the present invention is organized as follows:

1. Overview
2. Introduction
  - 25 2.1 Purpose and Scope
  - 2.2 Key Terms
3. Review of TR-059 Concepts
  - 3.1 Network Service Provider Network
    - 3.1.1 Description
  - 30 3.2 Application Service Provider Network
    - 3.2.1 Description
    - 3.2.2 Capabilities
  - 3.3 Regional Access Network
    - 3.3.1 Broadband Remote Access Server
    - 35 3.3.2 Access Network
    - 3.3.3 Access Node
  - 3.4 Evolution of the DSL Network
    - 3.4.1 Access Session Types



- 5    4.    QOS Capabilities of the Application Framework
  - 4.1    General Approach
  - 4.2    Classification
  - 4.3    Business Models for Supporting Concurrent NSP and ASP Access

Sessions

- 10                    4.3.1    Simple Bandwidth Partitioning
- 4.3.2    Priority and Dynamic Bandwidth Sharing
- 4.4    Considerations Associated with this Approach
  - 4.4.1    Static Classifiers
  - 4.4.2    Queue Structure

- 15    5.    Reference Data Model
  - 5.1    Subscriber Maintained Data
  - 5.2    Routing Gateway
  - 5.3    Regional/Access Network
  - 5.4    Application Service Provider
  - 20    5.5    Network Service Provider

- 6.    Reference Interface Specification and Detailed Message Flow
  - 6.1    Interface Between RG and Regional/Access Network
  - 6.2    Interface Between Regional/Access Network and ASP
  - 6.3    Interface Between Regional/Access Network and NSP
  - 25    6.4    Application Framework Infrastructure
    - 6.4.1    Framework Infrastructure Element Functional Description
    - 6.4.2    DSL Service Messaging Flow

- 7.    Future Capabilities of the Application Framework

- 8.    Example Use Scenario - Turbo Button

- 30    9.    Example Use Scenario - Video Conferencing

- 10.    Example Use Scenario - Gaming

- 11.    Application Flow Control Data

- 1.    **Overview**

35            This document defines a common application framework built on top of the DSL Forum TR-059 reference architecture that can be used in a common way to enable service providers to leverage bandwidth and QoS capabilities in the Regional/Access Network. This framework comprises an interface specification and

5 associated data model and mechanisms to control the QoS and bandwidth capabilities defined in TR-059. A common interface for Application Service Providers (ASPs) and Network Service Providers (NSPs) to leverage may reduce development costs and time to market. This interface defines a mechanism for applications to request IP QoS and bandwidth from the DSL Regional/Access network.

## 10 2. Introduction

### 2.1 Purpose and Scope

Recent work in the DSL Forum has documented a reference architecture, *DSL Evolution - Architecture Requirements for the Support of QoS-Enabled IP Services* (TR-059), with the purpose of defining a common way of supporting enhanced IP  
15 applications by enabling IP QoS and bandwidth management capabilities. TR-059 defines a common deployment architecture, set of interface specifications, and fundamental network element requirements. The architecture and requirements are largely "transport or network" layer focused. It may be useful to complement this work by defining a common higher-layer framework that leverages the capabilities of  
20 TR-059 and that can be used by application service providers (ASP) as they develop and deploy applications.

This document defines a common application framework built on top of the TR-059 reference architecture that can be used in a common way to enable service providers to leverage bandwidth and QoS capabilities in the Regional/Access  
25 Network. This framework comprises an interface specification and associated data model and mechanisms to control the QoS and bandwidth capabilities defined in TR-059. A common interface for ASPs and NSPs to leverage may reduce development costs and time to market. This interface defines a mechanism for applications to request IP QoS and bandwidth from the DSL Regional/Access network.

30 Specifically, the application framework is based on the capabilities defined in phase 2 of TR-059. Therefore, the framework defined here assumes that the capabilities of the access node in the Regional/Access network will remain largely unchanged, but does leverage a policy approach for *provisioning* the BRAS and Routing Gateway (RG) to manage IP flows appropriately. As real-time signaling  
35 capabilities become available this framework may be modified to support these capabilities. In defining the framework and providing details of its use, this document also intends to demonstrate that capabilities defined (here and in TR-059) are sufficient to support a reasonable set of applications.

5           Services that span Regional/Access networks and require inter-  
Regional/Access network communication are generally not described herein as part of  
this framework. Support of these services is possible if handled at the application  
layer where an ASP communicates to each Regional/Access network to establish  
bandwidth and QoS for a service.

## 10           2.2    Key Terms

The following definitions apply for the purposes of this document:

15	Access Network	The Access Network encompasses the elements of the DSL network from the NID at the customer premises to the BRAS. This network typically includes one or more Access Node type and often an ATM switching function to aggregate them.
20	Access Node	The Access Node contains the ATU-C, which terminates the DSL signal, and physically can be a DSLAM, Next Generation DLC (NG-DLC), or a Remote Access Multiplexer (RAM). A DSLAM hub can be used in a central office to aggregate traffic from multiple remote physical devices, and is considered logically to be a part of the Access Node. When the term "DSLAM" is used in this
25		document, it is intended to very specifically refer to a DSLAM, and not the more generic Access Node. The Access Node provides aggregation capabilities between the Access Network and the Regional Network. It is the first point in the network where
30		traffic on multiple DSL lines will be aggregated onto a single network.
	Application Flow	The set of packets associated with a particular application (e.g., video conferencing session, VoIP call, etc.).
35	Application Framework	A common reference data model and interface specification built on top of the TR-059 reference architecture that can be used in a common way to enable service providers to leverage bandwidth and QoS capabilities in the Regional/Access Network.
40	Auto Configuration Server (ACS)	A data repository that allows the Regional/Access network to provide configuration information to Routing Gateways (RG) in Customer Premises
45	Broadband Remote Access Server (BRAS)	The BRAS is the aggregation point for the subscriber traffic. It provides aggregation capabilities (e.g., IP, PPP, ATM) between the Regional/Access Network and the NSP or ASP. Beyond aggregation, it is also the injection point

5		for policy management and IP QoS in the Regional/Access Networks.
	Core Network	The center core of the Regional Network. The functions contained herein are primarily transport oriented with associated switching or routing capabilities enabling the proper distribution of the data traffic.
10		
	Downstream	The direction of transmission from the ATU-C (Access Node) to the ATU-R (modem).
	Edge Network	The edge of the Regional Network. The Edge Network provides access to various layer 2 services and connects to the Regional Network core enabling the distribution of the data traffic between various edge devices.
15		
	Loop	A metallic pair of wires running from the customer's premises to the Access Node.
20		
	Many-to-Many Access Sessions	The ability for multiple individual users or subscribers, within a single premises, to simultaneously connect to multiple NSPs and ASPs.
25		
	Regional Network	The Regional Network interconnects the Network Service Provider's network and the Access Network. A Regional Network for DSL connects to the BRAS, which is technically both in the Regional Network and in an Access Network. Typically, more than one Access Network is connected to a common Regional Network. The function of the Regional Network in this document goes beyond traditional transport, and may include aggregation, routing, and switching.
30		
	Regional/Access Network	The Regional and Access Networks – grouped as and end-to-end QoS domain and often managed by a single provider. The follow functional elements are contained in this network: Access Node, BRAS, and the ACS.
35		
	Routing Gateway	A customer premises functional element that provides IP routing and QoS capabilities. It may be integrated with or be separate from the ATU-R.
40		
	Rate Limit	A means to limit the throughput of a particular PPP session or application flow by either buffering (shaping) or dropping (policing) packets above a specified maximum data rate. The term bandwidth is used interchangeably with the concept of rate limiting. The bandwidth allocated to a PPP
45		

5		session or application is determined by the rate limit applied.
	Session	Session is typically an overloaded term. In this document it is intended to reference a PPP access session rather than a particular application flow.
10	Subscriber	Used to refer to the person that is billed for a service, like NSP access service or ASP services. The subscriber is considered the primary user of the service (see the definition of "user" below) and is the main account contact. The subscriber to an NSP access is referred to as a Network Subscriber and the subscriber to an application is referred to as an Application Subscriber.
15		
	Upstream	The direction of transmission from the ATU-R (modem) to the ATU-C (Access Node).
20		
	User	The person or entity that receives the benefit of a given service. The user may or may not be the subscriber of the service. A subscribed service has one or more users associated with the subscriber.
25		

### 3. Review of TR-059 Concepts

To provide a common reference for the application framework, an architectural view of the DSL network is provided. The text in this section is taken from TR-059 and provides a high level overview. For a more complete description refer to TR-059. **FIG. 1** illustrates the current state of deployed DSL networks. Boxes in the figures represent functional entities – networks and logical components rather than physical elements.

This traditional architecture is centered on providing service to a line or a loop. It is desired, however, to be able to provide services that are user-specific. Additionally, more than one subscriber can be present at the same premises and share a single loop. TR-059 describes a slightly more complex situation, and hides the common complexity shared with **FIG. 2**.

**FIG. 2** illustrates the components of a DSL access-based broadband network. **FIG. 2** indicates ownership of the components by different providing organizations. Boxes in the figures represent functional entities – networks and logical components rather than physical elements.

5           This model illustrates an architecture that provides services that are user-specific, *i.e.*, more than one subscriber can be present at the same premises and share a single loop. Note that **FIG. 2** shows many-to-many access through a common Regional/Access network. It is used to simultaneously provide an Application Service<sub>1</sub> between an ASP Network<sub>1</sub> and User<sub>1</sub> at the same time and over the same U  
10 interface as it supports a Network Service<sub>2</sub> between NSP Network<sub>2</sub> and User<sub>2</sub>.

### 3.1 Network Service Provider Network

#### 3.1.1 Description

The Network Service Provider (NSP) is defined as a Service Provider that requires extending a Service Provider-specific Internet Protocol (IP) address. This is  
15 the typical application of DSL service today. The NSP owns and procures addresses that they, in turn, allocate individually or in blocks to their subscribers. The subscribers are typically located in Customer Premises Networks (CPNs). The NSP service may be subscriber-specific, or communal when an address is shared using Network Address Port Translation (NAPT) throughout a CPN. This relationship  
20 among the NSP, A10-NSP interface, and Regional/Access Network is shown in **FIG. 2**. NSPs typically provide access to the Internet, but may also provide access to a walled garden, VPN, or some other closed group or controlled access network. L2TP and IP VPNs are typical A10-NSP interface arrangements.

The capabilities of the NSP may include, but are not limited to, for example:  
25 authenticating network access between the CPN and the NSP network; assignment of network addresses and IP filters; assignment of traffic engineering parameters; and/or customer service and troubleshooting of network access problems

### 3.2 Application Service Provider Network

#### 3.2.1 Description

30           The Application Service Provider (ASP) is defined as a Service Provider that uses a common network infrastructure provided by the Regional/Access Network and an IP address assigned and managed by the Regional Network Provider. This is a new type of DSL service. The Regional Network Provider owns and procures addresses that they, in turn, allocate to the subscribers. ASPs then use this common  
35 infrastructure to provide application or network services to those subscribers. For example, an ASP may offer gaming, Video on Demand, or access to VPNs via IPsec or some other IP-tunneling method. The ASP service may be subscriber-specific, or communal when an address is shared using NAPT throughout a Customer Premises

5 Network (CPN). It is envisioned that the ASP environment will have user-level rather than network-access-level identification, and that a common Lightweight Directory Access Protocol (LDAP) directory will assist in providing user identification and preferences. Logical elements used by ASPs typically include routers, application servers, and directory servers. The relationship between the ASP Network, the A10-  
10 ASP interface, and the Regional Network is shown in FIG. 2.

### 3.2.2 Capabilities

The capabilities of the ASP may include, but are not limited to, for example: authenticating users at the CPN; assignment of QoS to service traffic; customer service and troubleshooting of network access and application-specific problems;  
15 and/or ability to determine traffic usage for accounting purposes and billing.

### 3.3 Regional Access Network

The Regional/Access Network comprises the Regional Network, Broadband Remote Access Server, and the Access Network as shown in FIG. 3. Its primary function is to provide end-to-end data transport between the customer premises and  
20 the NSP or ASP. The Regional/Access Network may also provide higher layer functions, such as QoS and content distribution. QoS may be provided by tightly coupling traffic-engineering capabilities of the Regional Network with the capabilities of the BRAS.

#### 3.3.1 Broadband Remote Access Server

25 The BRAS performs multiple functions in the network. Its most basic function is to provide aggregation capabilities between the Regional/Access Network and the NSP/ASP. For aggregating traffic, the BRAS serves as a L2TP Access Concentrator (LAC), tunneling multiple subscriber Point-to-Point Protocol (PPP) sessions directly to an NSP or switched through a L2TS. It also performs aggregation for terminated PPP  
30 sessions or routed IP session by placing them into IP VPNs. The BRAS also supports ATM termination and aggregation functions.

Beyond aggregation, the BRAS is also the injection point for providing policy management and IP QoS in the Regional and Access Networks. The BRAS supports the concept of many-to-many access sessions. Policy information can be applied to  
35 terminated and non-terminated sessions. For example, a bandwidth policy may be applied to a subscriber whose Point-to-Point (PPP) session is aggregated into an L2TP tunnel and is not terminated by the BRAS. Sessions that terminate on (or are routed through) the BRAS, however, can receive per flow treatment because the BRAS has IP level awareness

5 of the session. In this model, both the aggregate bandwidth for a customer as well as the bandwidth and treatment of traffic per-application can be controlled.

### 3.3.2 Access Network

The Access Network refers to the network between the ATU-R and the BRAS including the access node and any intervening ATM switches.

### 10 3.3.3 Access Node

The Access Node provides aggregation capabilities between the Access Network and the Regional Network. It is the first point in the network where traffic on multiple DSL lines will be aggregated onto a single network. Traditionally the Access Node has been primarily an ATM concentrator, mapping PVCs from the  
15 ATU-R to PVCs in the ATM core. It has also shaped and policed traffic to the service access rates.

As described in TR-059, the responsibility of policing ATU-R to ATU-C PVCs to the subscribed line rate is moved from the Access Node to the BRAS to establish additional bandwidth on the DSL line for additional services. The Access  
20 Node sets the line rate for each PVC at the synch rate (or slightly less) of the ATU-R and ATU-C. This will make the maximum amount of subscriber bandwidth available for services. The BRAS polices individual sessions/flows as required to their required rates and also performs the dynamic changes when bandwidth-on-demand services are applied.

### 25 3.4 Evolution of the DSL Network

Phases 1 and 2 of TR-059 introduce the capability to change the Regional/Access network from an IP unaware layer 2 network to a network that leverages IP awareness in key elements to enable IP QoS and more efficient and effective use of bandwidth. These key IP aware elements are the BRAS and the RG  
30 as shown in FIG. 4.

FIG. 4 represents a paradigm shift in that the BRAS and the RG are now responsible for managing the traffic flow through the network. By enabling these devices to accept policy rules at subscriber session and application levels, IP flows can be managed in a more flexible and "dynamic" manner than previously possible.  
35 The BRAS is responsible for managing IP traffic in the downstream direction such that traffic is scheduled according to priority and in a way that ensures that congestion in the downstream network is reduced (*i.e.*, hierarchical scheduling). The RG



5 similarly, manages the scheduling of traffic in the upstream direction based on the  
 priority of the session and/or application. Given that the RG cannot be trusted, the  
 BRAS performs a policing function to ensure the upstream bandwidth in the access  
 network is utilized appropriately. Note that the priority and bandwidth policies can be  
 applied at the PPP session and or application levels; therefore, there is flexibility in  
 10 how traffic is treated in the network.

### 3.4.1 Access Session Types

The architecture also evolves the types and number of access sessions  
 (specifically PPP sessions) that a subscriber would typically establish to a service  
 provider. Where previously there had been just one access session to an ISP, there are  
 15 now multiple access sessions with three basic types:

Community NSP – Shown in FIG. 5 as the solid line between the RG and  
 NSP<sub>1</sub>, this type of access session is established between an RG and an NSP. It is  
 called the *Community* NSP connection because all the devices within the Customer  
 Premises Network share the connection to the NSP using the Network Port Address  
 20 Translation (NPAT) feature of the RG. Because the Community NSP connection is  
 given the *Default Route* at the RG there can typically be only one. This connection is  
 typically set up to an ISP to provide Internet access to all the devices in the Customer  
 Premises Network. This PPP session may terminate on the BRAS or may pass  
 through the BRAS in tact and be placed into a L2TP tunnel to the NSP.

25 Personal NSP – Shown in FIG. 5 as the dashed line between User<sub>1</sub> and NSP<sub>2</sub>,  
 this type of access session is established between a device within the Customer  
 Premises Network and an NSP. It passes through the RG at the Ethernet (PPPoE)  
 level. It is called the *Personal* NSP connection because only the device within the  
 Customer Premises Network from which the connection was established can access  
 30 the NSP. This connection may avoid using the NPAT feature of the RG. This  
 connection is typically set up to an ISP or a corporation to provide private or  
 personalized access, or any access that cannot traverse the NPAT sharing mechanism  
 at the RG. This PPP session may terminate on the BRAS or may pass through the  
 BRAS in tact and be placed into a L2TP tunnel to the NSP.

35 ASP – Shown in FIG. 5 as the dotted line between the RG and ASP<sub>1</sub>, this type  
 of access session is established between an RG and the ASP network. It is typically a  
 single connection that is shared by all the ASPs. Because the Community NSP  
 connection is typically given the *Default Route* at the RG, the ASP connection must

5 provide the RG with a list of routes to the ASP network. Also because there is not a default route to the ASP network, it may not be possible to provide typical Internet access through the ASP connection. This connection is typically set up to the ASP network to provide application-specific and QoS-enabled access among all the applications in the ASP network and all the devices in the Customer Premises  
10 Network. This PPP session type may terminate on the BRAS so that per application flow treatment can be applied.

#### **4. QOS Capabilities of the Application Framework**

##### **4.1 General Approach**

TR-059 describes a hierarchical scheduling approach leveraged by the BRAS  
15 to manage the downstream links between the BRAS and the RG. Similarly, it describes how the BRAS leverages policing techniques (including a random discard enhancement) to apply backpressure to the upstream source to minimize potential congestion in that direction. The application framework provides a mechanism for service providers to modify bandwidth and QoS. In particular embodiments of the  
20 present invention, to simplify the number of queues to be managed in the BRAS and RG, this framework assumes that only the ASP session has the ability to support per application flow treatment. In such embodiments, NSP access sessions can only be managed in terms of the aggregate bandwidth and priority with respect to other access sessions on the DSL line. Because many ASPs share the ASP access session, the  
25 bandwidth and priority of the session is set by the Regional/Access provider and typically cannot be modified by an ASP. The ASP can however modify the characteristics of specific applications within the ASP PPP session by assigning the application to a particular queue and treatment type. The BRAS and RG may schedule or police packets based on one or more of the following parameters: the  
30 priority of the access session; the current packet's relation to the rate limit of the access session; the priority of the application within the access session (only supported for the ASP PPP Session); and/or the current packet's relation to the rate limit of the application or queue, for example, an EF rate limit supported for the ASP PPP session.

35 Network resources are typically not reserved in this model. Instead, traffic engineering policies and intelligent scheduling and policing of packets is leveraged to achieve aggregate QoS characteristics. Similarly, the Differentiated Services (Diffserv) model is leveraged as a way to classify, mark, and schedule packets. The

- 5 QoS approach that has been applied to the application framework assumes that these capabilities are in place and that QoS relationships can be viewed within a single subscribers DSL "connection" (ATM VC) between the BRAS and the RG.

Further, if a pragmatic approach to providing QoS is taken, some additional simplifying assumptions can be made. It is expected that initially there will only be a small number of applications requiring QoS. The expected applications include VoIP, video conferencing, video on demand, and gaming. It is unlikely that the majority of DSL customers will subscribe to all of these services and expect to use them simultaneously. Rather, it is expected that only a small number of applications (*e.g.*, 2 or 3) will need to be managed concurrently on a DSL line basis. The expected applications also imply a certain priority relationship among themselves. If while playing an Internet game a VoIP call comes in, it may be generally agreed that the VoIP session should take precedence over the gaming session (if finishing the game is more important, then the user can choose not to answer the call). As long as these assumptions hold true, then a small number of applications can be managed effectively with a small number of queues and a simple priority arrangement among them. As the number of applications requiring QoS increases, however, these assumptions may have to change and the QoS approach may need to evolve to support a finer granularity.

The number of queues available for applications within the ASP PPP session is five, in accordance with some embodiments of the present invention. This may change over time, in accordance with other embodiments of the present invention, but initially the number of queues is likely to be small. Diffserv like treatment is assumed when describing the queue behaviors and can be classified as one expedited forwarding (EF) queue, up to 3 assured forwarding (AF) queues or one best effort (BE) queue. The EF queue typically receives the highest priority and is typically served first. This queue type is defined for constant bit rate type servers. A rate limit associated with this queue is put in place so it should not be able to consume all the DSL line resources. This queue will likely be reserved for voice applications. AF queues are defined for traffic that is more variable in nature and would be inefficient to associate with a fixed amount of network resources (EF). Queues in this category could receive different levels of priority or could simply be used as an aggregate priority but each queue may have a different rate limit applied depending on the requirements of the application using that queue. To simplify the approach, the

5 framework initially assumes the later case where AF queue receive a "medium" priority treatment and the different queues are used to provide different bandwidth needs (*i.e.* rate limits). A BE queue is the default queue and has resources available to it only after packets that are in profile for the EF and AF queue are served.

10 The approach to establishing QoS and bandwidth requirements in the network is one of provisioning rather than signaling. The BRAS and RG will be provisioned with the classifiers to identify flows and queue them appropriately. As a result the services that this model supports are services that fit more into a subscription model rather than an instantaneous establishment of service and QoS. This potential disadvantage, however, does not have to be apparent to the end users. Many services  
15 may require that the customer establish an account and perhaps even require the shipment of special hardware or software, for example, VoIP Phone, PC camera, and the like. During the time frame that the customer is establishing service with the ASP, the DSL network can be provisioned to support the service. It is important to note that the provisioning time lines are not expected to be in terms of days, but could  
20 be as small as a few minutes depending on how the application framework is implemented.

Given that a signaled approach to QoS is not included in the framework of certain embodiments of the present invention, real-time admission control cannot be accomplished at the network layer in such embodiments. While it could be possible  
25 to block the subscription of a new service based on the current, subscribed services, such a model may be too restrictive because it does not allow the user to subscribe to two applications that they would not intend on using simultaneously. Instead, a strict priority relationship among the applications flows is used to manage simultaneous application interactions. Rate limits are also applied at the RG and BRAS so that no  
30 single application can consume all the subscriber's DSL resources and to provide some level of fairness. An example application relationship, in accordance with some embodiments of the present invention, is shown in **FIG. 6** and **Table 1**. In this example, it is assumed that the NSP and PNSP sessions receive best effort treatment with respect to traffic that is in profile for the EF and AF queues in the ASP session.  
35 Other business models are possible as described in Section 4.3.

Application	Queue	Rate Limit of the Queue	Classification Parameters
VoIP			

Signaling	High Priority	100 Kbps	SIP Proxy IP Address & SIP
Bearer	High Priority	100 Kbps	Gateway IP Address & RTP
<b>Video Conf</b>			
Control Stream	High Priority	100 Kbps	SIP Proxy IP Address & SIP
Audio/Voice	High Priority	100Kbps	DSCP & MCU IP Address& RTP
Video	Medium Priority	384Kbps	DSCP & MCU IP Address & RTP
<b>Gaming</b>	Medium Priority	100k	Gaming Server IP Address
<b>HTTP</b>	Low Priority	None	Default

5

**Table 1 - Example Application Priority Relationship within the ASP Session**

FIG. 6 illustrates a queuing arrangement where there are five queues (EF, AF<sub>1</sub>, AF<sub>2</sub>, AF<sub>3</sub>, and BE) within the ASP session for per application treatment. In this arrangement, these queues can be characterized as high (EF), medium (AFs), and low priority (BE) treatment. Table 1 illustrates that voice will receive strict priority over other applications. Rate limits can be applied to each of the applications to ensure that a single application cannot starve out all other applications, but this requires dedicating a queue to each rate-limited application. Priority alone may not resolve all of the possible application interactions. In the example above, both the gaming and video conferencing video stream have the same priority. In the case that both applications are active they would compete over the first 100k of bandwidth available to the medium priority class. The rate limit associated with the AF<sub>2</sub> queue allows the video conferencing application to take precedence over the remaining resources up to its queue's rate limit. If the user experience for either the video stream or the game is unacceptable, the user will have to make their own admission control decision and pause or shut down the one they wish to have lower priority.

10

15

20

#### 4.2 Classification

There are two basic levels of classification that need to be applied in the framework: The first level is at the PPP session level. Classification at this layer is accomplished through inspection of the Fully Qualified Domain Name (FQDN) used when the PPP session is initiated. The second level is at the application layer – according to flows. To provide an application flow with the proper scheduling treatment, it is desirable to easily classify the flow. Classification of application flow may be accomplished using the header fields of the IP or Ethernet Packet (e.g., IP 5 tuple, DSCP, 802.1p). Using the interface specified in Section 6, ASPs may

25

30

5 communicate the classification information that is used in the BRAS and RG. This  
 same interface may be used to communicate the priority and desired bandwidth (rate  
 limit) to be associated with the classifier. In certain embodiments of the present  
 invention, this information is communicated at subscription time, and is not intended  
 to be established dynamically on a per-flow basis. As a result in such embodiments,  
 10 the classification information is expected to be static. The ASP may provide a well  
 known IP address, protocol, and/or Port to be used for classification purposes.

In particular embodiments of the present invention, within the customer  
 premises network (CPN), the CPE will be assigned private IP addresses from the RG.  
 When traffic leaves the CPN, the RG will perform NPAT enabling public routing of  
 15 the packets. The use of private addresses presents two issues: Given that the CPE  
 behind the RG will be using dynamic private addresses, they cannot be used as part of  
 the classification parameters. Secondly, many applications require signaling  
 messages to convey dynamic IP addresses and port numbers of media receivers in  
 their payloads. Existing static IP/transport layer policies may not be adequate in  
 20 supporting session endpoints separated by NAT and firewall entities. Therefore,  
 Application Layer Gateway (ALG) capabilities may be required at the RG for opening  
 and closing pinholes in the firewalls and maintaining the proper address translations  
 for dynamically created ports associated with flows created by session endpoints.  
 Some considerations with regard to ALG capabilities are discussed in the next  
 25 sections.

The BRAS can associate the IP address or ATM PVC of the RG with a  
 subscriber and then use the ASP's address to match the source or destination address  
 of the packets to properly classify the flow. At the customer premises, the RG can  
 match the ASP's address as the means of classifying the flow. Therefore, only the  
 30 ASPs IP address (and possibly port and protocol identifier) may be required for the bi-  
 directional flow to be classified correctly.

Certain types of applications may require additional information to capture the  
 flow. For these types of applications, the endpoints may need to provide additional  
 classification information in the IP packet header by marking the diffserv code point.  
 35 The use of diffserv code points (DSCP) may be standardized which may allow the  
 application to intelligently mark packets based on the expected treatment in the  
 network. DSCPs assigned by an untrusted entity can only be used after some edge  
 device has performed a check on the classification of the packet to ensure that it was

5 marked correctly. The RG may not be considered a trusted element and, therefore,  
the BRAS may need to police any classification performed by the RG - rather than  
simply accepting the DSCP that was provided. Depending on the relationship to the  
ASP, the Regional/Access network may be able to trust packets marked by the ASP.  
If the ASP is not trusted, either the BRAS or some other edge device may need to  
10 police the DSCPs.

#### **4.3 Business Models for Supporting Concurrent NSP and ASP Access Sessions**

**FIG. 7** illustrates several bandwidth relationships that can exist on an ADSL  
access loop. In **FIG. 7**, the outer circle represents the total bandwidth that is available  
15 within a virtual circuit on an ADSL line after the modems have been allowed to sync  
to a higher rate than is conventional. Within this total bandwidth there are two access  
sessions shown: an ASP Access Session and a NSP Access Session. The NSP Access  
Session, shown in light horizontal stripes, occupies a smaller space than the whole  
Virtual Circuit. This indicates that the NSP access session is not allowed to access the  
20 total bandwidth on the Virtual Circuit. Conventionally, the NSP Session and the  
Virtual Circuit would have been the same bandwidth. By increasing the sync rate on  
the DSL modems, additional bandwidth is created that exceeds that which the NSP  
has purchased.

The ASP access session has essentially the same set of bandwidth as the  
25 Virtual Circuit. This would indicate that some set of conditions exist where the ASP  
session could occupy all the bandwidth on the ADSL line. Several Applications are  
shown overlaid on the sessions and within the bandwidth limits assigned to the NSP  
and ASP. The NSP application (dark horizontal stripes) is a strict sub-set of the NSP  
Session and is using a large fraction of the NSPs allowed bandwidth. The three other  
30 applications, however, show three salient relationships and business models that can  
exist between applications in the ASP network and both applications as well as the  
access session for the NSP. These relationships will be described in the sections that  
follow.

##### **4.3.1 Simple Bandwidth Partitioning**

35 The first example is the Headroom Application and is shown in vertical  
stripes. This application is allowed to make use of only that bandwidth that the NSP  
could never access. In this type of model, a NSP is provided a dedicated amount of  
bandwidth on the access loop – even if there is not dedicated bandwidth through the

5 access network. In such an arrangement, ASP applications (or additional NSP access  
sessions) would only receive bandwidth to which the modems could sync that was  
over and above the rate sold to the NSP. In this arrangement, if the sync rate were at  
or below the rate sold to the NSP, no additional applications or access sessions could  
be provided. This arrangement may be unnecessarily restrictive and may be difficult  
10 to implement.

The second example is the Sharing Application (shown checkered). This  
application has access to all the bandwidth described by the headroom application, but  
also has access to additional bandwidth sold to the NSP, but not currently in use by  
applications in the NSP Session. A Sharing application can make use of all the  
15 bandwidth on the VC, but can only use the "NSP" bandwidth when the NSP session is  
not using it. Unlike the previous model, this application can receive bandwidth even  
when the sync rate is at or below the rate sold to the NSP. If the NSP applications are  
making use of all their bandwidth, however, then the result is similar to the  
arrangement described in the Headroom application. This arrangement could be  
20 described as work conserving, and may be used for simple bandwidth partitioning.

#### **4.3.2 Priority and Dynamic Bandwidth Sharing**

The third example is the Competing Application (shown in transparent gray).  
In this example, the application may have access to some or all of the bandwidth used  
by the NSP and it may have access to that bandwidth with greater, equal, or lesser  
25 precedence than the NSP applications. Similarly, this application may also be able to  
pre-empt bandwidth that other ASP applications are attempting to use. This is the  
most complex arrangement, and the most flexible. A competing application can  
compete for the bandwidth that NSP applications are attempting to use. Several cases  
of competing applications exist:

- 30 1. The first case is when a competing application has the same precedence as that  
of the NSP application(s). In this case, bandwidth is shared fairly according to  
a typical algorithm, like round-robin, or Weighted Fair Queuing (WFQ).  
Also, inter-application congestion avoidance mechanisms, like those that are  
part of TCP can decide how applications would share bandwidth in this case.
- 35 2. A second case is when a competing application has greater precedence than  
that of the NSP application(s). In this case, bandwidth is given to the  
competing application in strict priority – only "left-over" bandwidth is  
provided to the other applications. This is the highest QoS level, and may be



5 provided with an upper bound on the bandwidth that the application can obtain, *i.e.*, a *rate limit*. If the application exceeds the upper bound, its traffic will be dropped. This case is the most applicable to a VoIP application because it provides very low latency and because VoIP is not bursty to the point that the rate limit would be exceeded.

10 3. A third case is when a competing application has a combination of higher precedence and equal precedence. A rate, such as a committed information rate (CIR), is set and the application gets the same treatment as described in case 2 up to that rate. If the application bursts above CIR, then that traffic which bursts is treated differently; it must compete with the other applications as described in case 1.

15 4. A fourth case is when a competing application has a combination of higher precedence and lower precedence. A rate, such as a CIR, is set and the application gets the same treatment as described in case 2 up to that rate. If the application bursts above CIR, then that traffic which bursts is treated differently; it is treated like a sharing application – only receiving the leftover bandwidth that the NSP application does not use.

20 5. A fifth case is when a competing application has a combination of higher precedence, equal precedence and a strict rate limit. A rate, such as a CIR, and a second, higher rate, Peak information Rate (PIR), is set. The application gets the same treatment as described in case 3 up to the PIR rate. If the application bursts above PIR, then that traffic will be dropped.

25 6. Finally, there is a case when a competing application has a combination of higher precedence, equal precedence and lower precedence. As in case 5, a rate, such as a CIR, and a second, higher rate, such as a PIR, is set. The application gets the same treatment as described in case 3 up to the PIR rate. However, if the application exceeds the PIR, then that traffic is treated like a sharing application – only receiving the bandwidth that the NSP does not use.

30 These treatments can also be provided among ASP applications and with finer granularity among multiple applications.

#### 35 4.4 Considerations Associated with this Approach

##### 4.4.1 Static Classifiers

The following issues may be considered when using static classifiers:

- 5        1. There can only be one class of treatment per application. There is no sense of individual users within the residence using the same service, but desiring different levels of service.
2. Dynamic, commutative peer-to-peer applications cannot be easily captured.
3. Applications with multiple flows between the same destinations cannot be easily  
10        differentiated.

For applications like VoIP and video conferencing where the end points of a call may not be known a-priori, it is difficult to use a static classification scheme.

Below are several approaches to resolve these issues:

- 15        a. Force the application to some well-known IP address that can be used for classification purposes. This is true of a multipoint videoconference service that leverages a centralized (ASP provided) MCU or a VoIP call that is destined for a PSTN gateway or conference bridge. In both these cases, a static classifier can be used. This same approach could be leveraged for on-net or point-to-point video calls. These calls could be  
20        routed to utilize an MCU, conference bridge, or PSTN gateway even though they are not required for any other reason other than classification. There are vendors in the marketplace that have developed proxy devices for this purpose. This may be less resource efficient, however, than allowing the calls to flow point-to-point.
- 25        b. Classify based on protocol used. For example, classification based on the use of RTP could be used. Basing the classification on protocol alone, however, would enable other applications that use that same protocol to take advantage of QoS in the network without having to pay for it. Additionally, differentiation between application flows that use the same  
30        protocol may not be achieved (*e.g.*, voice and video using RTP).
- 35        c. Rely on the CPE to mark packets. In this case the IP phone or video conference application emits packets marked with the proper diffserv code point so that the RG and BRAS can classify based on that marking. Any application choosing to mark their traffic, however, would be able to take advantage of QoS in the network without having to pay for it.
- d. QoS aware Application Layer Gateway (ALG). Similar to the way ALGs have been developed for allowing signals to traverse NPAT and firewalls

5 by inspecting signaling messages, a QoS ALG may be created to inspect  
the signaling packets for SDP messages and to dynamically create  
classifiers during call setup. Given that initial signaling may be destined  
for a well known address, (SIP proxy) the ALG can be statically  
10 configured to treat all RTP flows set up using a given SIP proxy –  
regardless of the actual communicating peers. As the ALG inspects the  
packets to modify the RG's firewall rules, it can also be used to modify the  
RG's classification rules. This type of approach could be leveraged at the  
RG, where the number of sessions is small, but may present scaling issues  
if implemented in the BRAS.

- 15 e. Establish the classification information at call set up. This may require  
complex real time signaling mechanisms to be in place in the network to  
modify classifiers at call establishment and teardown.

Until a signaling approach is available, using an approach similar to that described  
in (a) appears to be the most reasonable from a technology and service offering  
20 perspective. A video conferencing ASP that does not provide centralized Media Control  
Unit (MCU) capabilities may only add limited value above that which is already available  
in the market. In the near term, most VoIP calls will likely be destined for PSTN  
gateways, and this arrangement provides a simple way to classify.

Differentiating applications with multiple flows between the same destinations, is  
25 typically seen within (but is not limited to) commutative services, like video conferencing.  
These applications typically have multiple flows (control/signaling, audio, and video)  
associated with a single application, and there may be a desire to treat them differently. As  
long as they use different well-known IP addresses or protocol types, then a static classifier  
can be used. Unfortunately, when the same protocol type is used (e.g., RTP for both audio  
30 and video) then there may not be a way to differentiate those streams if they are both  
destined for the same IP interface (e.g., MCU). Below are three approaches to resolve this  
issue:

- a. Require applications to use separate IP interfaces that expect differentiated  
treatment. An MCU, for example, could define one IP interface for video and  
35 another for audio. This would enable separate classification in the upstream and  
downstream direction in the RG and BRAS. Depending on the direction of the  
flow, either the source or destination can be used to match to the ASPs IP  
interfaces.

- 5        b. Rely on the application to mark packets. In this case, the videoconference application emits packets marked to the proper diffserv code point so that the RG and BRAS could classify based on that marking. As long as the packets are being transmitted to a well-known address, the classifier can use the combination of the DSCP and the destination IP. Given that there is a fixed IP address, no other
- 10       applications would be able to utilize the QoS intended for this application.
- c. Rely on knowledge of the actual RTP ports used by each of the flows to enable different treatments. This can be accomplished by statically assigning ports using a QoS ALG function as described above, or through the use of a signaling protocol.

15                    **4.4.2 Queue Structure**

      As the number of applications requiring QoS increases, so does the complexity of managing them in the access network. Over time, as more and more ASPs deploy applications requiring QoS and bandwidth management, the likelihood that multiple applications will be running simultaneously within the CPN may increase. The

20       complexity of managing these applications in a small number of queues with only three levels of precedence may become increasingly difficult given that there may no longer be a well-defined priority relationship among them. One approach would be to increase the number of queue types and behaviors. Diffserv defines four assured forwarding (AF) classes each with three levels of drop precedence. The addition of multiple AF classes to a

25       strict priority class (EF) and a low priority class (BE) already defined in the application framework can provide more granularity in queue and application behavior. It is unlikely, however, that the number of queues can be scaled with the number of applications available.

      While a limited number of additional queues may be available, their expected

30       behavior may become increasingly complex to describe. Unfortunately, to make use of these additional behaviors, applications must be able to define their requirements in a way that fits into this model. This becomes a challenge for two reasons: First, many applications do not understand that level of granularity and particularly will not understand what other applications will be vying for the DSL line resources. Secondly, describing the

35       inter-queue or inter-application behavior to ASPs so they can make use of these capabilities becomes more difficult as the number of queues increases without strictly defining the amount of resources reserved per queue. This difficulty is in part the result of

5 how diffserv was designed. Diffserv was not defined with the intent of managing per application flow behavior. Rather, it was defined to manage aggregate flow behaviors in the core of the network. As the number of simultaneous applications increases in the CPN and access network, the use of diffserv without resource reservation breaks down.

Leveraging a resource reservation approach can provide a mechanism for  
10 managing increasing numbers of applications. The reservation scheme need not necessarily require signaling. At subscription, time applications could reserve specific queues and could provide an intermediate solution. Longer term, as the number of applications continues to grow, a more dynamic reservation of resources will be required. In the dynamic case, applications may be able to reserve specific queues for the duration of  
15 the application flow, which will be released when they are done. In doing so, admission control to the DSL resources can be provided in a way that the applications behavior can be more clearly described. Use of Resource Reservation Protocol (RSVP) would provide an example of the former case. While having been defined for some time, actual RSVP implementations are elusive due to its general complexity and scaling limitations.  
20 Admission control provides one way to provide an application dedicated resources or to provide an indication when resources are not available. While conceptually attractive, it remains unclear if the complexity of such an approach is feasible.

## 5. Reference Data Model

In this section a description of the data required in each of the functional  
25 domains of the architecture (Regional/Access Network, RG, ASP, NSP, and subscriber) is presented. FIG. 8 illustrates a high level representation of the relationships between the different domains in accordance with some embodiments of the present invention. Based on this abstract view of the domains involved in providing an end-to-end service, a data model can be constructed.

30 Dotted lines 1 and 2 illustrated in FIG. 8 indicate that information is exchanged between the modules not specifically discussed with respect to the interface reference model. The dashed lines illustrated in FIG. 8 indicate a physical connection and the solid lines illustrated in FIG. 8 indicate that information is exchanged within the scope of the interface reference model. In particular, lines 1 and  
35 2 illustrate exchanges between the subscriber and the NSP and ASP, respectively, when the subscriber, for example, signs up for service. Line 3 illustrates the configuration of the RG by the Regional/Access Network. It will be understood that

5 this may only be for the initial install. The ACS located with in the Regional/Access Network may handle all subsequent configuration changes. Line 4 illustrates the initiation of access sessions that are terminated in the DSL network. The ACS located with in the Regional/Access Network may communicate with the RG for configuration updates. Finally, lines 5 and 6 of FIG. 8 illustrate communication  
 10 between the NSP/ASP and the DSL network that establishes a DSL connection. The ASP and NSP may also communicate bandwidth and QoS changes per session or application.

FIG. 9 depicts a UML model capturing the type of data used to support bandwidth and QoS management in accordance with some embodiments of the  
 15 present invention. This model is provided for illustration purposes only and is not intended to represent a complete deployment implementation, which may use a wider scope of information beyond bandwidth and QoS. FIGS. 10 through 12 provide additional details within the main domains, in accordance with some embodiments of the present invention, and are described below. The remainder of this section  
 20 provides a detailed description of the data records and attributes captured in the presented UML model.

### 5.1 Subscriber Maintained Data

The following data elements are maintained at Subscriber Premises (this record is maintained by the subscriber - it could be stored on a PC or any other  
 25 storage device/media) in accordance with some embodiments of the present invention:

Record Type	Elements	Description	Source
NSPSubscriber PPP Session Record 970		The subscribers need to know their DSL_line_ID, NSPSubscriber_ID and NSPSubscriber_Password for accessing their NSP networks. Only a single NSP PPP session record can exist.	
	DSL_Line_ID	DSL_Line_ID is a unique identifier for the DSL line. Currently the TN is used as such an identifier.	DSL_Line_ID is provided by the Regional/Access Network Provider at subscription time.
	NSPSubscriber_ID	This ID is used for accessing the NSP networks.	Assigned by the NSP at the time of subscription
	NSPSubscriber_Password	Subscriber_Password is initially set by the NSP, later it can be changed by the Subscriber. It is used together with the NSPSubscriber_ID to access the NSP networks.	Initially assigned by the NSP at subscription time. Can be changed by the subscriber.

Personal NSPSubscriber PPP Session Record 974		The subscribers need to know their DSL_line_ID, PersonalNSPSubscriber_ID and Personal NSPSubscriber_Password for accessing their Personal NSP network. Multiple records can exist.	
	DSL_Line_ID	As defined above	As defined above
	PersonalNSPSubscriber_ID	This ID is used for accessing the Personal NSP networks.	Assigned by the Personal NSP at the time of subscription.
	PersonalNSPSubscriber_Password	It is used together with the PersonalNSPSubscriber_ID to access the PNSP networks.	Initially assigned by the PNSP at the time of subscription. Can be changed by the subscriber.
ASPSubscriber PPP Session Record 972		The subscribers need to know their DSL_line_ID, ASPSubscriber_ID and ASPSubscriber_Password for accessing their ASP services. For each application they subscribe to, they need to maintain their User_ID and Password. Only one ASP PPP session record can exist.	
	DSL_Line_ID	As defined above	As defined above
	ASPSubscriber_ID	This ID is used for accessing the ASP networks.	Provided by ASP at the time of subscription
	ASPSubscriber_Password	It is used together with the ASPSubscriber_ID to access the ASP networks.	Initially assigned by ASP at the time of subscription. Can be changed by the subscriber.
User Account Record 976, 978, 980		This record is maintained by user/users of services provided over the Regional/Access Network. A user account is tied to a subscriber account. Multiple user accounts can be associated with a single subscriber account. Note: There is one or multiple User Account Record under each of the NSPSubscriber PPP Session Record, Personal NSPSubscriber PPP Session Record, and ASPSubscriber PPP Session Record.	Created at the time of subscription to ASP services
	User_ID	This ID is used for accessing the given service.	Assigned by a given ASP to a particular user at the time subscription
	User_Password	It is used together with the User_ID to access a given service.	Initially assigned by a given ASP to a particular user at the time of subscription. Can be changed by the subscriber.

5

## 5.2 Routing Gateway

Routing Gateway is a customer premises functional element that provides IP routing and QoS capabilities. The main functions of the RG may include one or more of: IP routing between the CPN and the Access Network; multi-user, multi-destination support (Multiple simultaneous PPPoE sessions (started from the RG or from devices inside the CPN) in conjunction with non-PPP encapsulated IP (bridged) sessions); network Address Port Translation (NAPT); PPPoE pass through; multiple queues with scheduling mechanism; and/or IP QoS.

The following data elements are maintained at the RG in accordance with some embodiments of the present invention:

15

Record Type	Elements	Description	Source
Routing Gateway Record 902		Routing Gateway Record is maintained by RG.	It is initialized with the initial configuration by the manufacturer or configured by the user during the install process. The ACS can also update this record during and after the initial install.
	DSL_Line_ID	As defined above	As defined above
	DSL_Sync_Rate	DSL_Sync_Rate is the current physical layer synch rate of the DSL line. This record includes both upstream and downstream metrics. It also includes what is the maximum obtainable synch rate	It is populated by RG during modem training.
NSP PPP Session Record 904		NSP PPP Session Record is maintained by the RG to store information specific to the community NSP access session. This session is launched by the RG and provides the CPN with a default route. Only one community NSP record can exist.	
	NSPSubscriber_ID	This ID is used for accessing the DSL and NSP networks.	Assigned by NSP at subscription time.
	NSPSubscriber_Password	It is used together with the Subscriber_ID to access the DSL and NSP networks.	NSPSubscriber_Password is initially set by the NSP, later it can be changed by the Subscriber.
	Session_Classifier	This parameter contains classification parameters to identify the NSP PPP session (i.e. Ethertype and FQDN).	This value is populated based on configuration data received from the ACS.
	Session_Priority	Optional - Indicates the priority level of the NSP PPP connection relative to the other PPP sessions present – only required if DSL bandwidth is shared across PPP sessions and need to establish a priority relationship across the PPP sessions	This value is populated based on configuration data received from the ACS.
	Session_Bandwidth	The Session_Bandwidth contains information about the maximum bandwidth assigned to this NSP PPP access session.	This value is initialized based on a default value or on the Profile Data received from the ACS.
ASP PPP Session Record 906		ASP PPP Session Record is maintained by the RG to store information specific to the ASP access session. This PPP session is launched by the RG and receives routes, via RIP, to the ASP network. Only one ASP record can exist.	
	ASPSubscriber_ID	This ID is used for accessing the ASP network (and potentially ASP applications although the RG would not be involved).	Assigned by ASP at subscription time
	ASPSubscriber_Password	It is used together with the ASPSubscriber_ID to access the Regional/Access Network. (and potentially ASP applications although the RG would not be involved)	Initially set by the ASP, later it can be changed by the Subscriber
	Session_Classifier	This parameter contains classification parameters to identify the ASP PPP session (i.e. Ethertype and FQDN).	This value is populated based on configuration data received from the ACS.
	Session_Priority	Optional - Indicates the priority level of the ASP PPP connection relative to the other PPP sessions present – only required if DSL bandwidth is shared across PPP sessions and need to establish a priority relationship across the PPP sessions	This value is populated based on configuration data received from the ACS.
	Session_Bandwidth	The Session_Bandwidth contains information about the maximum bandwidth (upstream and downstream) assigned to this ASP PPP access session.	This value is populated based on configuration data received from the ACS.
Application Flow Record 910		The Application Flow Record is maintained by the RG for each application service that subscriber or users of the DSL line subscribe to. It is used to store application specific data. Multiple application records can exist.	
	Flow_Classifier	Flow_Classifier contains classification parameters to identify the application flow (IP 5 tuple).	This value is populated based on configuration data received from the ACS.
	Flow_Priority	Indicates the priority level of the application	This value is populated based on



		within the ASP PPP connection. This parameter indicates the treatment of the application flow (what queue it should be placed in) as well as any marking requirements (DSCP).	configuration data received from the ACS.
	Flow_Bandwidth	Flow_Bandwidth parameter is assigned to the given application based on the negotiated value between the ASP and the Regional/Access Network. It indicates the maximum upstream and downstream bandwidth. It is used by the RG to shape and police the application flow.	This value is populated based on configuration data received from the ACS.
Personal NSP PPP Session Record 908		Personal NSP PPP Session Record is maintained by the RG to store information specific to the Personal NSP access session. Multiple records can exist.	
	Session_Classifier	This parameter contains classification parameters to identify the PNSP PPP session (i.e. Ethertype and FQDN).	This value is populated based on configuration data received from the ACS.
	Session_Priority	Optional - Indicates the priority level of the PNSP PPP connection relative to the other PPP sessions present - only required if DSL bandwidth is shared across PPP sessions and need to establish a priority relationship across the PPP sessions.	This value is populated based on configuration data received from the ACS.
	Session_Bandwidth	The Session_Bandwidth contains information about the maximum bandwidth assigned to the PNSP access service.	This value is populated based on configuration data received from the ACS.

5

### 5.3 Regional/Access Network

The primary function of the Regional/Access Network is to provide end-to-end data transport between the customer premises and the NSP or ASP. The Regional/Access Network may also provide higher layer functions, such as QoS and bandwidth management. QoS may be provided by tightly coupling traffic-engineering capabilities of the Regional Network with the capabilities of the BRAS.

10

The following data elements are maintained at the Regional/Access Network in, for example, a Regional/Access Network Record 920 in accordance with some embodiments of the present invention:

Record Type	Elements	Description	Source
DSL Line Record 922		The DSL line record is maintained in the Regional/Access Network and is unique to each DSL line. It maintains data specific to a DSL line and the sessions that traverse it.	
	DSL_Line_ID	As defined above	As defined above
	DSL_Sync_Rate	DSL_Sync_Rate is the current physical layer synch rate of the DSL line. This record includes both upstream and downstream metrics. It also includes what are the maximum obtainable data rates in either direction.	This data is obtained from the DSLAM EMS and the RG
NSP PPP Session Record 926		NSP PPP Session Record is maintained by the Regional/Access Network to store information specific to the community NSP PPP access sessions. The NSP access record is tied to the DSL Line Record. Only one can exist.	
	SP_ID	Uniquely identifies the NSP that the subscriber has a relationship with. Used to cross reference users to NSPs who make turbo/QoS requests.	Assigned by the Regional/Access Network Provider when a wholesale relationship is established with the NSP
	Session_Classifier	This parameter contains classification	Provided by the NSP at

		parameters to identify the NSP PPP session (i.e. Ethertype and FQDN).	subscription time.
	Session_Priority	Optional - Indicates the priority level of the NSP PPP connection relative to the other PPP sessions present – only required if DSL bandwidth is shared across PPP sessions and need to establish a priority relationship across the PPP sessions	The Regional/Access Network Provider initializes this value at subscription time based on the business model and type of wholesale access that is being sold to the NSP and its relationship to the ASP or the PNSP sessions.
	Session_Bandwidth	The Session_Bandwidth contains information about the maximum bandwidth (upstream and downstream) assigned to this NSP PPP session.	This value is set by the NSP.
PersonalNSP PPP Session Record 930		PersonalNSP PPP Session Record is maintained by the Regional/Access Network to store information specific to the Personal NSP PPP access sessions. Multiple records can exist.	
	SP_ID	As defined above	As defined above
	Session_Classifier	This parameter contains classification parameters to identify the PNSP PPP session (i.e. Ethertype and FQDN).	Provided by the NSP at subscription time.
	Session_Priority	Optional - Indicates the priority level of the PNSP PPP connection relative to the other PPP sessions present – only required if DSL bandwidth is shared across PPP sessions and need to establish a priority relationship across the PPP sessions	The Regional/Access Network Provider initializes this value at subscription time based on the business model and type of wholesale access that is being sold to the NSP and its relationship to the ASP or the PNSP sessions. Assigned by PNSP and passed to Regional/Access network via NNI message interface.
	Session_Bandwidth	The Session_Bandwidth contains information about the maximum bandwidth (upstream and downstream) assigned to this PNSP PPP session.	This value is initially set by the PNSP.
ASP PPP Session Record 928		ASP PPP Session Record is maintained by the Regional/Access Network to store information specific to the ASP PPP session. The ASP PPP Record is tied to the DSL Line Record. Only one ASP record can exist.	
	SP_ID	As defined above	As defined above
	Session_Classifier	This parameter contains classification parameters to identify the ASP PPP session (i.e. Ethertype and FQDN).	Provided by the ASP at subscription time
	Session_Priority	Optional - Indicates the priority level of the ASP PPP connection relative to the other PPP sessions present – only required if DSL bandwidth is shared across PPP sessions and need to establish a priority relationship across the PPP sessions	The Regional/Access Network Provider initializes this value at subscription time based on the business model and type of wholesale access that is being sold to the NSP and its relationship to the ASP or the PNSP sessions. Assigned by ASP and passed to Regional/Access network via NNI message interface.
	Session_Bandwidth	The Session_Bandwidth contains information about the maximum bandwidth (upstream and downstream) assigned to this ASP PPP session.	This value is initially set by the Regional/Access Network Provider, but could be modified by individual ASPs that request more bandwidth for their application. An alternative model is that this value is set to the max value initially and ASPs only affect their allotment of bandwidth within the PPP

			session.
Application Flow Record 932		The Application Flow Record contains specific details about an application within the ASP session. This record is tied to the ASP account record. Many application records can be associated with an ASP account record.	
	Flow_Classifier	Flow_Classifier contains classification parameters to identify the application flow (IP 5 tuple). It is used by the BRAS & the RG.	Values provided by the ASP.
	Flow_Priority	Indicates the priority level of the application within the ASP PPP connection. This parameter indicates the treatment of the application flow (what queue it should be placed in) as well as any marking requirements (DSCP). It is used by the BRAS and the RG.	Provided by the ASP. Regional/Access Network Provider provides available options to select.
	Flow_Bandwidth	Flow_Bandwidth parameter is assigned to the given application based on the negotiated value between the ASP and the Regional/Access Network. It indicates the maximum upstream and downstream bandwidth. It is used by the BRAS & the RG to shape and police the application flow.	These values are provided by the ASP to meet the needs of the application.
Service Provider Record 924		The service Provider Record is used to authenticate service providers (NSPs, ASPs) who wish to query the Regional/Access Network for information and make bandwidth and or QoS requests.	
	SP_ID	As defined above	As defined above
	SP_Credentials	Used to authenticate this service provider together with SP_ID when connecting to the Regional/Access Network.	Assigned by the Regional/Access Network Provider
	Authorization	Represents what records the SP has access to (DSL line records can it make queries/modifications to)	Assigned by the Regional/Access Network Provider
	CDR_Data	Stores billing data for wholesale access to Turbo and QoS controls	This data is generated by the Regional/Access Network Provider

5

#### 5.4 Application Service Provider

The Application Service Provider (ASP) is defined as a Service Provider that shares a common infrastructure provided by the Regional/Access Network and an IP address assigned and managed by the Regional Network Provider. In particular

10 embodiments of the present invention, the ASP provides one or more of: application services to the subscriber (gaming, video, content on demand, IP Telephony, etc.); service assurance relating to this application service; additional software or CPE; and/or a contact point for all subscriber problems related to the provision of specific service applications and any related subscriber software. However, the ASP may not

15 provide or manage the assignment of IP address to the subscribers.

The following data elements may be maintained at the ASP in accordance with some embodiments of the present invention:

5

Record Type	Elements	Description	Source
ASP Record 960		ASP Record is maintained by each service provider. This record contains the service provider's name, password, and other related information that identifies this unique ASP and is used to communicate with Regional/Access Network Provider.	
	ASP_ID	Used to uniquely identify an ASP that has a business relationship with Regional/Access Network Provider.	Assigned by Regional/Access Network Provider at the time of connecting the ASP to the ASP network.
	ASP_Credentials	Used to authenticate an ASP together with ASP_ID when a service session is established with a Regional/Access Network Provider.	Assigned by Regional/Access Network Provider at the time of connecting the ASP to the ASP network.
ASP Subscriber Record 962		ASP Subscriber Record is maintained by ASP that provides the application service. This record uniquely identifies the subscriber and service related data.	
	DSL_Line_ID	As defined above	As defined above
	ASPSubscriber_ID	This ID is used for accessing the DSL and ASP networks.	Assigned by the ASP at the time of subscription.
	ASPSubscriber_Password	It is used together with the ASPSubscriber_ID to access the ASP application. Note: The ASP Subscriber ID and Password are only used by ASP for its own purpose and will not be used or referenced by Regional/Access Network for authentication purpose. It is just for maintaining ASP data integrity.	Assigned by the ASP at the time of subscription.
	Session_Classifier	Local copy of Regional/Access Network ASP PPP Session Classification info.	Acquired from the Regional/Access Network through the ANI interface.
	Session_Priority	Local copy of Regional/Access Network ASP PPP Session Priority info.	Acquired from the Regional/Access Network through the ANI interface.
	Session_Bandwidth	Local copy of the Regional/Access Network ASP PPP Session Bandwidth Info.	Acquired from the Regional/Access Network through the ANI interface.
Application Flow Control Record 966		This record is maintained by the ASP and used to store application specific information such as bandwidth arrangement and QoS settings. This record is tied to the ASP bandwidth Record. Multiple Application Record can be associated with one single ASP bandwidth record.	
	Flow_Classifier	Flow_Classifier contains classification parameters to identify the application flow (IP 5 tuple). It is used by the BRAS & the RG.	Values provided by the ASP.
	Flow_Priority	Indicates the priority level of the application within the ASP PPP connection. This parameter indicates the treatment of the application flow (what queue it should be placed in) as well as any marking requirements (DSCP). It is used by the BRAS and the RG.	Provided by the ASP. The Regional/Access Network Provider specifies available options to select.
	Flow_Bandwidth	Flow_Bandwidth parameter is assigned to the given application based on the negotiated value between the ASP and the Regional/Access Network Provider. It indicates the maximum upstream and downstream bandwidth. It is used by the BRAS & the RG to shape and police the application flow.	These values are provided by the ASP to meet the needs of the application.
ASP User Account 964		This record is maintained by the ASP. An ASP user account is tied to an ASP subscriber account. Multiple user accounts can be associated with a single subscriber account.	
	User_ID	This ID is used for accessing the given service.	Assigned by a given ASP to a particular user.
	User_Password	It is used together with the User_ID to access a given service.	User_Password is initially assigned by an ASP. Can be changed by the user.

5

### 5.5 Network Service Provider

The Network Service Provider (NSP) is defined as a Service Provider that requires extending a Service Provider-specific Internet Protocol (IP) address. This is the typical application of conventional DSL service. The NSP owns and procures addresses that they, in turn, allocate individually or in blocks to their subscribers. The subscribers are typically located in Customer Premises Networks (CPNs). The NSP service may be subscriber-specific, or communal when an address is shared using NAPT throughout a CPN. The NSP may include Internet Service Providers (ISPs) and Corporate Service Providers (CSPs); may be responsible for overall service assurance; may provide CPE, or software to run on customer-owned CPE, to support a given service; may provide the customer contact point for any and all customer related problems related to the provision of this service; and/or may authenticate access and provides and manages the assignment of IP address to the subscribers.

The following data elements are maintained at the NSP in accordance with some embodiments of the present invention:

Record Type	Elements	Description	Source
NSP Record 940, 950		NSP Record is maintained by each NSP. This record contains the service provider's name, password, and other related information that identifies this unique service provider and is used communicate with access NSP.	
	NSP_ID	Uniquely identifies the NSP that the subscriber has a relationship with. Used to cross reference users to NSPs who make turbo/QoS requests	Assigned by Regional/Access Network Provider at the time of connecting the NSP.
	NSP_Credentials	Used to authenticate this NSP together with NSP_ID when a service session is established with a DSL access network for requesting a network service.	Assigned by Regional/Access Network Provider at the time of connecting the NSP.
NSP Subscriber Record 942, 952		NSP Subscriber Record is maintained by NSP that provides the network service. This record uniquely identifies the subscriber and service related data.	
	DSL_Line_ID	As defined above	As defined above
	NSPSubscriber_ID	This ID is used for accessing the DSL and NSP networks.	Assigned to a DSL subscriber by the NSP.
	NSPSubscriber_Password	It is used together with the NSPSubscriber_ID to access the NSP application. Note: The NSP Subscriber ID and Password are only used by NSP for its own purpose and will not be used or referenced by Regional/Access Network for authentication purpose. It is just for maintaining the NSP data integrity.	Assigned by the ASP at the time of subscription.
	Session_Classifier	Local copy of Regional/Access Network NSP PPP Session Classification info	Acquired from the Regional/Access Network through the NNI interface.
	Session_Priority	Local copy of Regional/Access Network NSP PPP Session Priority info.	Acquired from the Regional/Access Network through the NNI interface.
	Session_Bandwidth	Local copy of the Regional/Access Network ASP PPP Session Bandwidth Info.	Acquired from the Regional/Access Network

			through the NNI interface.
NSP User Account 944, 954		This record is maintained by the NSP. A NSP user account is tied to an NSP subscriber account. Multiple user accounts can be associated with a single subscriber account.	
	User_ID	This ID is used for accessing the given service.	Assigned by a given NSP to a particular user.
	User_Password		User_Password is initially assigned by a NSP. Can be changed by the user.

5

## 6. Reference Interface Specification and Detailed Message Flow

This interface reference specification defines an interface between the Regional/Access Network and a Network Service Provider (NSP), a Personal NSP (PNSP), and an Application Service Provider (ASP) as well as an interface between  
10 the Regional/Access Network and Routing Gateway (RG) for enabling the NSP/PNSP/ASP to utilize the bandwidth and QoS management capabilities provided by the Regional/Access Network in their NSP/PNSP/ASP applications, in accordance with some embodiments of the present invention.

### 6.1 Interface Between RG and Regional/Access Network

15 This section defines the messaging interface between the Regional/Access Network and the Routing Gateway, in accordance with some embodiments of the present invention. This interface does not define any message for RG or ACS authentication assuming both of them are part of the DSL Network infrastructure.

#### 20 1. UpdateSessionBandwidthInfo(DSL\_Line\_ID, SP\_ID, Session\_Classifier, Session\_Priority, Session\_Bandwidth)

This message is sent from the Regional/Access Network to a specified RG (via ACS) as a notification when new bandwidth and QoS information for a PPP session becomes available. The bandwidth and QoS related parameters include  
25 Session\_Classifier, Session\_Priority, and Session\_Bandwidth. These parameters will be stored in the NSP PPP Session Record, PNSP PPP Session Record, or ASP PPP Session Record depending on the SP\_ID. These session records are defined in the DSL Data Reference Model.

**DSL\_Line\_ID:** Subscriber's line identification.

30 **SP\_ID:** The identifier of service provider requesting for service. The service provider can only be NSP, PNSP, or ASP.

**Session\_Classifier:** PPP session classifier.

**Session\_Priority:** Session priority indicator.

- 5    **Session\_Bandwidth:** Bandwidth data including upstream bandwidth and downstream bandwidth.

**2. UpdateSessionBandwidthAck(DSL\_Line\_ID, SP\_ID)**

10        This message is sent from the RG to the Regional/Access Network (via ACS) as an acknowledgement of receiving the update session bandwidth information notification.

**DSL\_Line\_ID:** Subscriber's line identification.

**SP\_ID:** The identifier of service provider requesting for service. The service provider can only be NSP, PNSP, or ASP.

15

**3. UpdateAppFlowControlInfo(DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth)**

20        This message is sent from the Regional/Access Network to a specified RG (via ACS) as a notification of new bandwidth and QoS info for application flow becoming available. The parameters including Flow\_Classifier, Flow\_Priority, and Flow\_Bandwidth will replace the existing data stored in the Application Flow Control Record defined in the Regional/Access Data Reference Model.

**DSL\_Line\_ID:** Subscriber's line identification.

25        **SP\_ID:** The identifier of service provider requesting for service. The service provider can only be NSP, PNSP, or ASP.

**Flow\_Classifier:** Application flow classifier.

**Flow\_Priority:** Priority queue indicator.

**Flow\_Bandwidth:** Flow bandwidth information for shaping and policing.

30    **4. UpdateAppFlowControlAck(DSL\_Line\_ID, SP\_ID)**

      This message is sent from the RG to the Regional/Access Network (via ACS) as an acknowledgement of receiving the update application flow control info notification.

**DSL\_Line\_ID:** Subscriber's line identification.

35        **SP\_ID:** The identifier of service provider requesting for service. The service provider can only be NSP, PNSP, or ASP.

5    **5. UpdateSessionBandwidthRequest(DSL\_Line\_ID, SP\_ID)**

      This message is sent from the RG to the Regional/Access Network (via ACS) as a request for obtaining the PPP session level of the bandwidth and QoS settings stored at the Regional/Access Network for the specified subscriber line.

**DSL\_Line\_ID:** Subscriber's line identification.

10    **SP\_ID:** The identifier of service provider requesting for service. The service provider can only be NSP, PNSP, or ASP.

**6. UpdateSessionBandwidthResponse(DSL\_Line\_ID, SP\_ID, Session\_Classifier, Session\_Priority, Session\_Bandwidth, Return\_Code)**

15       This message is sent from the Regional/Access Network to the RG (via ACS) as a response for getting the PPP session level of the bandwidth and QoS settings request.

**DSL\_Line\_ID:** Subscriber's line identification.

**SP\_ID:** The identifier of service provider requesting for service. The service provider  
20    can only be NSP, PNSP, or ASP.

**Session\_Classifier:** PPP session classifier.

**Session\_Priority:** Session priority indicator.

**Session\_Bandwidth:** Session bandwidth information including upstream bandwidth and downstream bandwidth.

25    **Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

**7. UpdateAppFlowControlRequest(DSL\_Line\_ID, SP\_ID)**

      This message is sent from the RG to the Regional/Access Network (via ACS) as a request for obtaining the application flow level of the bandwidth and QoS settings stored at the Regional/Access Network for the specified subscriber line.

**DSL\_Line\_ID:** Subscriber's line identification.

**SP\_ID:** The identifier of service provider requesting for service. The service provider can only be NSP, PNSP, or ASP.

35

**8. UpdateAppFlowControlResponse(DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth, Return\_Code)**



5           This message is sent from the Regional/Access Network to the RG (via ACS) as a response for getting the application flow level of the bandwidth and QoS settings request.

**DSL\_Line\_ID:** Subscriber's line identification.

**SP\_ID:** The identifier of service provider requesting for service. The service provider  
10       can only be NSP, PNSP, or ASP.

**Flow\_Classifier:** Application flow classifier.

**Flow\_Priority:** Priority queue indicator.

**Flow\_Bandwidth:** Flow bandwidth information for shaping and policing.

**Return\_Code:** Return code from the DSL Network, indicating if the request is  
15       accomplished successfully.

## **6.2     Interface Between Regional/Access Network and ASP**

          This section defines the messaging interface between the Regional/Access Network and the Application Service Providers, in accordance with some embodiments of the present invention.

20

### **1.   EstablishServiceSessionRequest (SP\_ID, SP\_Credentials)**

          This message is sent from an ASP to the Regional/Access Network as a request for establishing a communication session. All the ASPs need to be authenticated by the Regional/Access Network before the network bandwidth and  
25       QoS service capabilities can be accessed. With this request, the ASP can specify a life span of this session by providing a life span parameter that could be imbedded in the SP\_Credentials. When the specified life span expires, the ASP must resend this request to establish a new service session.

**SP\_ID:** Service Provider Identification. **SP\_Credentials:** Service Provider  
30       Credentials.

### **2.   EstablishServiceSessionResponse (Authorization, Return\_Code)**

          This message is sent from the Regional/Access Network to the service provider as a response for the communication session establishment request. The  
35       Regional/Access Network returns an authorization code indicating what services and resources are authorized for the service provider to access.

**Authorization:** Authorization code indicating what Regional/Access Network resources is authorized for the service provider to access.

- 5    **Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

**3. CreateAppFlowControlRecordRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth)**

- 10        This message is sent from an ASP to the Regional/Access Network as a request for creating an application specific flow control record defined as Application Flow Control Record in DSL Data Model. The initial settings are provided with Flow\_Classifier, SP\_ID, Flow\_Priority, and Flow\_Bandwidth.

**Authorization:** Authorization code obtained when the service session is established.

- 15    **DSL\_Line\_ID:** Subscriber's line identification.

**SP\_ID:** The identifier of service provider requesting for service. The service provider can only be ASP.

**Flow\_Classifier:** 5-tuple (source IP address, source port, destination IP address, destination port, protocol type) identifying a unique application flow.

- 20    **Flow\_Priority:** Priority queue setting

**Flow\_Bandwidth:** Flow bandwidth information for shaping and policing.

**4. CreateAppFlowControlRecordResponse (DSL\_Line\_ID, Return\_Code)**

- 25        This message is sent from the Regional/Access Network to the ASP as a response for the creation of the application flow control record request.

**DSL\_Line\_ID:** Subscriber's line identification.

**Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

- 30    **5. DeleteAppFlowControlRecordRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifier)**

This message is sent from an ASP to the Regional/Access Network as a request for deleting an Application Flow Control Record defined in DSL Data Model.

**Authorization:** Authorization code obtained when the service session is established.

- 35    **DSL\_Line\_ID:** Subscriber's line identification.

**SP\_ID:** The identifier of service provider requesting for service. The service provider can only be ASP.

**Flow\_Classifier:** Identifier of an application flow.

5

**6. DeleteAppFlowControlRecordResponse (DSL\_Line\_ID, Return\_Code)**

This message is sent from the Regional/Access Network to the ASP as a response for the deletion of the application flow control record request.

**DSL\_Line\_ID:** Subscriber's line identification.

10 **Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

**7. ChangeAppFlowControlRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth)**

15 An ASP can send this message to the Regional/Access Network as a request for changing the Priority and Shaping Data defined in the Application Flow Control Record of the DSL Data Model.

**Authorization:** Authorization code obtained when the service session is established.

**DSL\_Line\_ID:** Subscriber's line identification.

20 **SP\_ID:** The identifier of service provider requesting for service. The service provider should be an ASP.

**Flow\_Classifier:** Application traffic flow identifier.

**Flow\_Priority:** The application priority queue indicator for replacing the existing settings.

25 **Flow\_Bandwidth:** Flow bandwidth information for replacing the existing settings.

**8. ChangeAppFlowControlResponse (DSL\_Line\_ID, Return\_Code)**

This message is sent from the Regional/Access Network to the service provider as a response for the bandwidth change request. A Return\_Code is sent back  
30 indicating whether the change is successful.

**DSL\_Line\_ID:** Subscriber's line identification.

**Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

35 **9. QueryAppFlowControlRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifier)**

- 5           An ASP can send this message to the Regional/Access Network as a request for querying the application specific priority and shaping information contained in the Application Flow Control Record.

**Authorization:** Authorization code obtained when the service session is established.

**DSL\_Line\_ID:** Subscriber's line ID.

- 10 **SP\_ID:** Identifier of the service provider requesting for bandwidth and priority information.

**Flow\_Classifier:** Identifier of an application flow.

- 15 **10. QueryAppFlowControlResponse (DSL\_Line\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth, Return\_Code)**

This message is sent from the Regional/Access Network to the service provider as a response for the bandwidth info request. The bandwidth data record is returned.

**DSL\_Line\_ID:** Subscriber's line identification.

- 20 **Flow\_Classifier:** Identifier of an application flow.

**Flow\_Priority:** Current priority queue setting.

**Flow\_Bandwidth:** Current bandwidth setting for shaping and policing.

**Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

- 25 **11. QuerySessionBandwidthRequest (Authorization, DSL\_Line\_ID, SP\_ID)**

An ASP, can send this message to the Regional/Access Network as a request for querying the PPP session bandwidth and priority information associated with the specified DSL\_Line\_ID. The data is stored in ASP PPP Session record defined in the

- 30 DSL Data Model.

**Authorization:** Authorization code obtained when the service session is established.

**DSL\_Line\_ID:** Subscriber's line ID.

**SP\_ID:** Identifier of the service provider requesting for bandwidth and priority information.

- 35 **12. QuerySessionBandwidthResponse (DSL\_Line\_ID, Session\_Classifier, Session\_Priority, Session\_Bandwidth)**

5           This message is sent from the Regional/Access Network to the service provider as a response for the bandwidth info request. The bandwidth data record is returned.

**DSL\_Line\_ID:** Subscriber's line identification.

**Session\_Classifier:** PPP session classifier used to identify PPP session traffic flow.

10 **Session\_Priority:** Current Priority queue setting.

**Session\_Bandwidth:** Current session bandwidth setting.

### **13. TerminateServiceSessionRequest (SP\_ID, Authorization)**

15           This message is sent from an ASP to the Regional/Access Network as a request for terminating a communication session.

**SP\_ID:** Service Provider Identification.

**Authorization:** Authorization code indicating what Regional/Access Network resources is authorized for the service provider to access.

### **20 14. TerminateServiceSessionResponse (SP\_ID, Return\_Code)**

          This message is sent from the Regional/Access Network to the service provider as a response for the communication session termination request.

**SP\_ID:** Service Provider Identification.

25 **Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

## **6.3 Interface Between Regional/Access Network and NSP**

30           This section defines the messaging interface between the Regional/Access Network and Network Service Provider, in accordance with some embodiments of the present invention.

### **1. EstablishServiceSessionRequest (SP\_ID, SP\_Credentials)**

35           This message is sent from a NSP to the Regional/Access Network as a request for establishing a communication session. The NSPs need to be authenticated by the Regional/Access Network before the network bandwidth and QoS service capabilities can be accessed. With this request, the NSP can specify a life cycle of this session by providing a life span parameter imbedded in the SP\_Credentials. When the specified life span expires, the NSP must resend this request to establish a new service session.

**SP\_ID:** Service Provider Identification.

5 **SP\_Credentials:** Service Provider Credentials.

**2. EstablishServiceSessionResponse (Authorization, Return\_Code)**

This message is sent from the Regional/Access Network to the service provider as a response for the communication session establishment request. The

10 Regional/Access Network returns an authorization code indicating what services and resources are authorized for the service provider to access.

**Authorization:** Authorization code indicating what Regional/Access Network resources is authorized for the service provider to access.

15 **Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

**3. ChangeSessionBandwidthRequest (Authorization, DSL\_Line\_ID, SP\_ID, Session\_Classifier, Session\_Priority, Session\_Bandwidth)**

20 A NSP can send this message to the Regional/Access Network as a request for changing the PPP session bandwidth and priority information associated with the specified DSL\_Line\_ID. The data is stored in the NSP PPP Session Record defined in the DSL Data Model.

**Authorization:** Authorization code obtained when the service session is established.

**DSL\_Line\_ID:** Subscriber's line identification.

25 **SP\_ID:** Identifier of service provider requesting for service.

**Session\_Classifier:** PPP session classifier used to identify PPP session traffic flow.

**Session\_Priority:** Session priority indicator setting to replace the current one.

**Session\_Bandwidth:** Session bandwidth information for replacing the existing one.

30 **4. ChangeSessionBandwidthResponse (DSL\_Line\_ID, Return\_Code)**

This message is sent from the Regional/Access Network to the service provider as a response for the bandwidth change request. A Return\_Code is sent back indicating whether the change is successful.

**DSL\_Line\_ID:** Subscriber's line identification.

35 **Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

**5. QuerySessionBandwidthRequest (Authorization, DSL\_Line\_ID, SP\_ID)**

- 5           A NSP can send this message to the Regional/Access Network as a request for querying the PPP session bandwidth and priority information associated with the specified DSL\_Line\_ID. The data is stored in the NSP PPP Session Record defined in the DSL Data Model.

**Authorization:** Authorization code obtained when the service session is established.

- 10 **DSL\_Line\_ID:** Subscriber's line ID.

**SP\_ID:** Identifier of the service provider requesting for bandwidth and priority information.

- 6. QuerySessionBandwidthResponse (DSL\_Line\_ID, Session\_Classifier, Session\_Priority, Session\_Bandwidth)**

This message is sent from the Regional/Access Network to the service provider as a response for the bandwidth info request. The bandwidth data record is returned.

**DSL\_Line\_ID:** Subscriber's line identification.

- 20 **Session\_Classifier:** PPP session classifier used to identify PPP session traffic flow.

**Session\_Priority:** Current Priority queue setting.

**Session\_Bandwidth:** Current session bandwidth setting.

**7. TerminateServiceSessionRequest (SP\_ID, Authorization)**

- 25           This message is sent from an NSP to the Regional/Access Network as a request for terminating a communication session.

**SP\_ID:** Service Provider Identification.

**Authorization:** Authorization code indicating what Regional/Access Network resources is authorized for the service provider to access.

- 30 **8. TerminateServiceSessionResponse (SP\_ID, Return\_Code)**

This message is sent from the Regional/Access Network to the service provider as a response for the communication session termination request.

**SP\_ID:** Service Provider Identification.

- 35 **Return\_Code:** Return code from the Regional/Access Network, indicating if the request is accomplished successfully.

**6.4 Application Framework Infrastructure**

5 An Application Framework Infrastructure, in accordance with some embodiments of the present invention, is illustrated in **FIG. 13** and is a reference implementation model for enabling the ASP, NSP, and/or Personal NSP to utilize the bandwidth and QoS management capabilities. This framework infrastructure is supported by seven functional elements, including ANI Protocol Handler, NNI Protocol Handler, UNI Protocol Handler,  
10 DSL Service Manager, DSL Session Data Store, Provision Interface, and BRAS Adapter, in accordance with some embodiments of the present invention. For realizing the DSL network bandwidth and QoS management capabilities, this infrastructure may interact with the Routing Gateway via an Automated Configuration Server (ACS) and the BRAS to set appropriate policies upon receiving a request from the ASP, NSP, or PNSP, as  
15 depicted in **FIG. 13**.

The communication interface between the Regional/Access Network and an ASP is defined as the Application-to-Network Interface (ANI). The communication interface between the Regional/Access Network and a NSP or PNSP is defined as the Network-to-Network Interface (NNI) as discussed above with respect to the Regional/Access Interface.  
20 Through this framework infrastructure, the ASP, NSP, and/or PNSP can use the DSL Network bandwidth and QoS management capabilities to create their bandwidth and QoS "aware" applications. To enable the communication and service creation, a DSL Service API may be defined as a part of the Regional/Access Application Framework Infrastructure. This API may be a reference procedural implementation of the ANI and  
25 NNI.

Any suitable communication interface between the application framework and the BRAS and ACS may be utilized and, therefore, will not be discussed in detail herein. An interface may be used at these points and may be defined as part of the network element requirements. The use of Common Open Policy Service (COPS) is  
30 an example standard interface that may be implemented at these points to push changes into the ACS and BRAS.

#### **6.4.1 Framework Infrastructure Element Functional Description**

This section describes the main functions of each element of the Application Framework Infrastructure as illustrated in **FIG. 13**, in accordance with some  
35 embodiments of the present invention.

##### ANI Protocol Handler

The ANI Protocol Handler takes a request message from the ASP application, passes the request to the DSL Service Manager, waits for the response from the DSL



- 5 Service Manager, and sends the response message back to the ASP that requests the service. The protocol used in this prototype is the Application-to-Network Interface defined in this proposal.

NNI Protocol Handler

- 10 The NNI Protocol Handler takes a request message from the NSP/PNSP application, passes the request to the DSL Service Manager, waits for the response from the DSL Service Manager, and sends the response message back to the NSP/PNSP that requests the service. The protocol used in this prototype is the Network-to-Network Interface defined in this proposal.

UNI Protocol Handler

- 15 The UNI Protocol Handler passes the bandwidth and QoS related parameters via the ACS to a Routing Gateway associated with a subscriber. Because the Routing Gateway obtains its provisioning parameters from the ACS with a soon to be industry standard interface (WAN-Side DSL Configuration specification), this same interface may be used to communicate bandwidth and QoS information to the RG.

20 DSL Service Manager

- The DSL Service Manager behaves as a service broker that provides one or more of the following functions: allows ASP/NSP/PNSP to set and query bandwidth and QoS data associated with a PPP session, and to create, change, and delete application flow control record associated with each individual application; interacts  
25 with BRAS to pass bandwidth and QoS related data and policies for prioritizing, shaping, and policing subscriber's traffic flow either associated with a PPP session or an individual application flow; and/or communicates with ACS to pass bandwidth and QoS related data and policies to a specified Routing gateway working together with BRAS for prioritizing, shaping, and policing the subscriber's traffic flow at the access  
30 network.

DSL Session Data Store

- This is the Master Database maintaining the DSL data model described in section 4.3. It stores all the bandwidth and QoS related data and policies that can be queried, modified, created, and deleted by the ASP/NSP/PNSP through the ANI/NNI  
35 interface. The following records are maintained in the DSL Session Data Store in accordance with some embodiments of the present invention: a DSL Line Record; an NSP PPP Session Record; a Personal NSP PPP Session Record; an ASP PPP Session Record; and/or an application Flow Control Record.

5           This master copy is replicated in the BRAS and ACS network elements with appropriate data records. The BRAS copy of the data may include the following records in accordance with some embodiments of the present invention: an NSP PPP Session Record; a personal NSP PPP Session Record; an ASP PPP Session Record; and/or an Application Flow Control Record.

10           The ACS network element may include a replica of the following records in accordance with some embodiments of the present invention: an NSP PPP Session Record; a personal NSP PPP Session Record; an ASP PPP Session Record; and/or an Application Flow Control Record.

#### DSL Service API

15           This service creation API is used by the ASP/NSP for creating their bandwidth and QoS "aware" applications. This API directly maps the ANI/NNI protocol defined in this proposal into procedures, methods, and/or other software embodiments, for example, to facilitate application programming.

#### 20   Provisioning Interface

          This is a GUI based interface to allow the DSL Service Provider to provision the bandwidth and QoS settings for each individual subscriber based on subscriber telephone number, and provision the ASP/NSP that have a business arrangement with the DSL service provider. The data model for support of the provisioning has been  
25   defined herein.

#### **6.4.2 DSL Service Messaging Flow**

          This section provides several service scenarios to demonstrate how the messaging interface may be used by an ASP application in accordance with some embodiments of the present invention.

30

#### Service Provider Authentication Scenario Messaging Flow

          FIG. 14 illustrates the messaging flow for the application authentication scenario in accordance with some embodiments of the present invention.

##### **(1) EstablishServiceSessionRequest (SP\_ID, SP\_Credentials)**

35           This message is sent from the ASP/NSP to the DSLNetwork as a request for establishing a communication session. The ASP/NSP needs to be authenticated by the Regional/Access Network before any network service can be provided.

Processing Steps:

- 5 a) ANI/NNI Protocol Handler receives the request message and passes the request to DSL Service Manager
- b) DSL Service Manager finds the corresponding Service Provider Record by querying DSL Session Data Store based on the SP\_ID
- 10 c) DSL Service Manager validates the SP\_Credentials. A result of authentication is sent back to the ASP/NSP via ANI/NNI Protocol Handler.
- If the authentication is passed, a valid Authorization code is sent back. Otherwise, an invalid Authorization code is returned.

**(2) EstablishServiceSessionResponse (Authorization, Return\_Code)**

- 15 This message is sent from Regional/Access Network to ASP/NSP as a response for the service session establishment request.

**(3) TerminateServiceSessionRequest (SP\_ID, Authorization)**

- This message is sent from the ASP/NSP to the DSL Network as a request for
- 20 terminating the communication session.
- a) ANI/NNI Protocol Handler receives the request message and passes the request to DSL Service Manager.
- b) DSL Service Manager finds the corresponding communication session, terminates the session, and release all the session related resources.
- 25 c) DSL Service manager sends a result back to the ASP/NSP via ANI/NNI Protocol Handler.

**(4) TerminateServiceSessionResponse (SP\_ID, Return\_Code)**

- This message is sent from Regional/Access Network to ASP/NSP as a response for
- 30 the service session termination request.

Application Level Bandwidth and QoS Query Scenario Messaging Flow

FIG. 15 illustrates the messaging flow for the application level bandwidth and QoS query scenario in accordance with some embodiments of the present invention.

- 35 (1) QueryAppFlowControlRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifer)

This message is sent from the ASP to the DSL Network as a request for inquiring the bandwidth and QoS information associated with the specified DSL line.

5 Processing Steps:

- a) ANI Protocol Handler receives the request message and passes the request to DSL Service Manager
- b) DSL Service Manager finds the corresponding DSL Line Record, ASP PPP Session Record, and Application Flow Record(s) to collect the requested information.
- c) DSL Service Manager sends the collected bandwidth and QoS info back to the ASP via ANI Protocol Handler.

15 (2) **QueryAppFlowControlResponse (DSL\_Line\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth, Return\_Code)**

This message is sent from Regional/Access Network to ASP as a response for inquiring the bandwidth and QoS info request.

Application Level Bandwidth and QoS Modification Scenario Messaging Flow

20 FIG. 16 illustrates the messaging flow for the application level bandwidth and QoS query modification scenario in accordance with some embodiments of the present invention.

(1) **ChangeAppFlowControlRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth)**

25 This message is sent from the ASP to the Regional/Access Network as a request for changing the bandwidth and QoS data associated with the specified DSL line.

Processing Steps:

- a) ANI Protocol Handler receives the request message and passes the request to DSL Service Manager
- b) DSL Service Manager validates the authorization code based on corresponding Service Provider record, finds the corresponding DSL Line Record, ASP PPP Session Record, and Application Flow Record(s) to set the bandwidth and QoS data as requested by the ASP.
- c) DSL Service Manager communicates with BRAS Adapter for passing related bandwidth and QoS data to BRAS.

- 5 d) BRAS Adapter communicates with BRAS for setting the data in BRAS own data repository.
- e) DSL Service Manager notifies RG (via ACS) of new bandwidth and QoS info becoming available by sending the message of
- 10 **UpdateAppFlowControlInfo(DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth)** through UNI Protocol Handler.
- f) UNI Protocol Handler passes the new bandwidth and QoS data to a specified RG via ACS.
- g) ACS sends a response message back to UNI Protocol Handler to confirm the data is received.
- 15 h) UNI Protocol Handler sends the message
- UpdateAppFlowControlAck(DSL\_Line\_ID, SP\_ID)** back to DSL Service Manager as a response.
- i) DSL Service Manager sends the response message back to ASP via ANI Protocol Handler.
- 20 j) ACS notifies the specified RG of the availability of new bandwidth/QoS data via WAN-Side DSL Config Interface.
- k) The specified RG receives notification and downloads the new data from ACS.

**(2) ChangeAppFlowControlResponse (DSL\_Line\_ID, Return\_Code)**

- 25 This message is sent from Regional/Access Network to ASP as a response for setting the bandwidth and QoS request.

Application Flow Control Record Creation Scenario Messaging Flow

- 30 **FIG. 17** illustrates the messaging flow for the application flow control record creation scenario in accordance with some embodiments of the present invention.

**(1) CreateAppFlowControlRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth)**

This message is sent from the ASP to the Regional/Access Network as a request for creating an Application Flow Control Record for a specified subscriber.

35 Processing Steps:

- a) ANI Protocol Handler receives the request message and passes the request to DSL Service Manager

- 5 b) DSL Service Manager validates the authorization code based on corresponding Service Provider record, finds the corresponding DSL Line Record, ASP PPP Session Record, and then creates and sets an Application Flow Control Record as requested by the ASP.
- 10 c) DSL Service Manager communicates with BRAS Adapter for passing related bandwidth and QoS data to BRAS.
- d) BRAS Adapter communicates with BRAS for setting the data in BRAS own data repository.
- 15 e) DSL Service Manager notifies RG of new bandwidth and QoS becoming available by sending the message of **UpdateAppFlowControlInfo(DSL\_Line\_ID, SP\_ID, Flow\_Classifier, Flow\_Priority, Flow\_Bandwidth)** via UNI Protocol Handler.
- f) UNI Protocol Handler passes the new bandwidth and QoS data to a specified RG via ACS.
- 20 g) ACS sends a response message back to UNI Protocol Handler to confirm the data is received.
- h) UNI Protocol Handler sends the message **UpdateAppFlowControlAck(DSL\_Line\_ID, SP\_ID)** back to DSL Service Manager as a response.
- i) DSL Service Manager sends the response message back to ASP via ANI Protocol Handler.
- 25 j) ACS notifies the specified RG of the availability of new bandwidth/QoS data via WAN-Side DSL Config Interface.
- k) The specified RG receives notification and downloads the new data from ACS.

30 **(2) CreateAppFlowControlResponse (DSL\_Line\_ID, Return\_Code)**

This message is sent from DSL Network to ASP as a response for creating the application flow control record request.

Application Flow Control Record Deletion Scenario Messaging Flow

35 **FIG. 18** illustrates the messaging flow for the application flow control record deletion scenario in accordance with some embodiments of the present invention.

**(1) DeleteAppFlowControlRecordRequest (Authorization, DSL\_Line\_ID, SP\_ID, Flow\_Classifier)**

- 5            This message is sent from the ASP to the DSLNetwork as a request for deleting an Application Flow Control Record for a specified application.

Processing Steps:

- a) ANI Protocol Handler receives the request message and passes the request to DSL Service Manager
- 10    b) DSL Service Manager finds the corresponding DSL Line Record and associated the ASP PPP Session Record. Delete the App Flow Control Record based on the Flow\_Classifier.
- c) DSL Service Manager sends a response back to ASP as a confirmation.

15    **(2) DeleteAppFlowControlRecordResponse (DSL\_Line\_ID, Return\_Code)**

This message is sent from Regional/Access Network to ASP as a response for deletion of App Flow Control Record request.

NSP PPP Session Level Bandwidth and QoS Modification Scenario Messaging Flow

- 20            **FIG. 19** illustrates the messaging flow for the PPP session level-bandwidth and QoS modification scenario in accordance with some embodiments of the present invention.

**(1) ChangeSessionBandwidthRequest (Authorization, DSL\_Line\_ID, SP\_ID, Session\_Classifier, Session\_Priority, Session\_Bandwidth)**

- 25            This message is sent from the NSP to the Regional/Access Network as a request for changing the PPP session level of bandwidth and QoS data associated with the specified DSL line.

Processing Steps:

- a) NNI Protocol Handler receives the request message and passes the request to DSL Service Manager
- 30            b) DSL Service Manager validates the authorization code based on the corresponding Service Provider record, finds the corresponding DSL Line Record, and the NSP/PNSP PPP Session Record to set the bandwidth and QoS data as requested by the NSP.
- 35            c) DSL Service Manager communicates with BRAS Adapter for passing the bandwidth and QoS data to BRAS.
- d) BRAS Adapter communicates with BRAS for setting the data in BRAS own data repository.

- 5 e) DSL Service Manager notifies RG of new bandwidth and QoS being available by sending a notification to NNI Protocol Handler.
- f) NNI Protocol Handler passes the new bandwidth and QoS data associated with a specified RG to ACS by sending the following message to ACS.  
UpdateSessionBandwidthinfo(DSL\_Line\_ID, SP\_ID, Session\_Classifier,  
10 Session\_Priority, Session\_Bandwidth).
- g) ACS sends a response message back to NNI Protocol Handler to confirm the data is received by sending the following message.  
UpdateSessionBandwidthAck(DSL\_Line\_ID, SP\_ID)
- h) UNI Protocol Handler passes the acknowledgement back to DSL Service Manager  
15 as a response.
- i) DSL Service Manager sends the following response message back to NSP via NNI Protocol Handler.  
ChangeSessionBandwidthResponse(DSL\_Line\_ID, Return\_Code)
- j) ACS notifies the specified RG of the availability of new bandwidth/QoS data via  
20 WAN-Side DSL Config Interface.
- k) The specified RG receives notification and downloads the new bandwidth and QoS data from ACS.

**(2) ChangeSessionBandwidthResponse (DSL\_Line\_ID, Return\_Code)**

- 25 This message is sent from Regional/Access Network to NSP as a response for changing the PPP level of the bandwidth and QoS request.

ASP/PPP Session Level Bandwidth and QoS Query Scenario Messaging Flow

- FIG. 20 illustrates the messaging flow for the PPP session level bandwidth and  
30 QoS query scenario in accordance with some embodiments of the present invention.

**(1) QuerySessionBandwidthRequest (Authorization, DSL\_Line\_ID, SP\_ID)**

- This message is sent from the ASP/NSP to the Regional/Access Network as a request for inquiring the bandwidth and QoS information associated with the  
35 specified DSL line.

Processing Steps:



- 5 a) ANI/NNI Protocol Handler receives the request message and passes the request to  
DSL Service Manager
- b) DSL Service Manager finds the corresponding DSL Line Record and the ASP/NSP  
PPP Session Record to collect the requested information.
- c) DSL Service Manager sends the collected bandwidth and QoS info at PPP session  
10 level back to the ASP/NSP via ANI/NNI Protocol Handler.

**(2) QuerySessionBandwidthResponse (DSL\_Line\_ID, Session\_Classifier,  
Session\_Priority, Session\_Bandwidth, Return\_Code)**

This message is sent from Regional/Access Network to ASP/NSP as a  
response for inquiring the bandwidth and QoS info request.

15

**7. Future Capabilities of the Application Framework**

- Exemplary embodiments of the invention have been described above with  
respect to an Application Framework comprising a reference data model and an  
interface specification defined for specific transport flows related to QoS and  
20 bandwidth capabilities. This Application Framework may be expanded, in  
accordance with some embodiments of the present invention to support other services  
that link network services, telecommunications information technology, and  
customers including, for example: registration - enables the ASP to register  
services/applications with the Regional/Access Network; discovery - enables the  
25 Subscriber to discover services/applications within the Regional/Access Network;  
subscription - enables the ASP to manage and maintain subscriber accounts;  
management - for validation of subscribers and related services/applications; session -  
enables the xSP to manage and maintain session establishment, Management: session  
control, and session teardown for subscriber access to services/applications;  
30 authentication - enables the xSP to validate the user/subscriber for network access and  
services/applications access - who are you?; authorization - enables the xSP to  
validate the user/subscriber for network access and services/applications access - what  
permissions do you have?; profile - enables the xSP to manage and maintain  
user/subscriber profile data; identify - enables the xSP to manage and maintain user  
35 preferences, profiles, identity data; presence - enables the xSP to know and maintain  
awareness of the current existence of the subscriber; notification - enables the xSP to  
notify the subscriber of related services/applications information; and/or billing -  
enables the xSP to capture subscriber/user billing data for network usage and

5 services/applications usage for mediating a common billing record. These other capabilities may provide a host of centralized software services supporting a distributed network computing environment linking users/subscribers to their desired services and applications.

8. **Example Use Scenario - Turbo Button**

10 A source of potential frustration for users of data services is that data rates supported by the network (e.g., 1.5 Mb/s downstream and 256 Kb/s upstream) are often not properly matched with application requirements. Even with the higher speeds afforded with DSL access, users of many applications (e.g., content download such as large MS Office service packs or movie trailers, and on-line gaming) may be  
15 interested in using a service that would provide an even higher access speed at the times they need it most by invoking a "Turbo Button" service. The higher access speed limit is achieved via a service profile change that eliminates or lessens artificially imposed limits on the achievable speed in the user's PPP session. This section shows how the DSL Application Framework can support such a service, in accordance with some embodiments of the present invention, starting with the  
20 reference model shown in FIG. 21.

Many implementations of a Turbo Button service are possible in accordance with various embodiments of the present invention. For the purposes of this section, we will work with a fairly simple implementation in which the service is provisioned  
25 by an NSP called myNSP.com. The user requests the turbo button service at the community NSP's website during a browsing session at normal speed. Note that other ordering mechanisms are possible including mechanisms that are separate from the DSL session, e.g., using a telephone or a mass-distributed CD.

As mentioned above in certain embodiments of the present invention, the  
30 service is implemented via provisioning rather than by using real-time signaling. Under this assumption, a provisioning cycle is initiated after the user invokes the service and the provisioning completes before the effect is seen. Another result of this assumption is that the effect of the user's service invocation is permanent, i.e., once turbo speed is in place, it lasts until the user cancels the service and another  
35 provisioning cycle occurs to reinstate the default service parameters. Real-time signaling may be needed to support a service that supports on-demand, brief turbo sessions on an as needed basis.

5           Once the user requests the turbo service, the NSP queries the Regional/Access network to find out what turbo options can be presented to the user. The NSP may map the available upgrades to marketing categories (e.g., fast, faster, wickedly fast). The user selects one of the options, and the NSP requests the profile from the Regional/Access network that supports the requested speed. The Regional/Access network in turn pushes  
10   new policy (e.g., classifiers, rate limiters, priority) into the user's RG that will support the higher speed. It is important to note that the service is still "Best Effort," *i.e.*, there is no assumption of a QoS guarantee at this time. A version of turbo button service with QoS support may be implemented in accordance with other embodiments of the present invention.

15           We will assume that the NSP authenticates its own users for services such as Turbo Button. A centralized authentication service (as well as other ancillary services such as billing and presence functionality) could be implemented in the Regional/Access network on behalf of NSPs and ASPs in accordance with additional embodiments of the present invention. In a typical business model, the NSP might bill the user for usage of the  
20   turbo button service. In turn, the DSL network provider would bill the NSP for carrying traffic across the Regional/Access network at turbo speeds.

#### Turbo Button Scenario Description

25           **FIG. 22** illustrates an example of the sequence of events occurring with using the Turbo Button Service to access sites via a network service provider called "myNSP.com." For simplicity of illustration, the details of the Regional/Access network (DSL Service Manager, UNI and ANI protocol handlers, ACS, BRAS, etc.) are not shown – the expanded flows were shown in Section 6.4. The step numbers shown in the figure correspond with the list provided below.

- 30
1. The user clicks an advertisement to reach the NSP's Turbo Button subscription menu.
  2. The NSP host authenticates itself with the Regional/Access network in order to be able to access the customer profile it wants to update.
  - 35   3. Once authenticated, the NSP host then queries the Regional/Access network for available options for the users access session connection. It uses the

- 5 response to this query to put together a set of options for presentation to the customer.
4. The user selects one of the options.
5. The NSP requests the Regional/Access network to change the session bandwidth associated with the access session. A notification may be sent to the user
- 10 indicating that the turbo button provisioning is under way and that turbo speed will be available later that day (for example).
6. Using Update Session Bandwidth messaging, the Regional/Access network pushes new policy to the RG that will support the turbo speed.
7. Once the new policy is in place, the user is able to enjoy turbo speed access to
- 15 sites served by the NSP. Note that all users connected to the access session (*i.e.*, other PC users on the household LAN) would also enjoy the benefits of the turbo button service.
8. Later, the user decides to cancel turbo button service.
9. Steps 5 and 6 are repeated with the profile and policy put in place being those
- 20 needed for default access session speeds.
10. The network has returned to its previous state and the user's PPP session is no longer turbo'd.

**9. Example Use Scenario - Video Conferencing**

- 25 This section illustrates how the DSL Application Framework can support a videoconference service in accordance with some embodiments of the present invention. The videoconferencing model used is a SIP-driven service implemented by an ASP with a centralized control/mixing conference server. This is the tightly coupled model being developed by an IETF Sipping WG design team that uses four
- 30 logical entities: focus, conference state notification service, conference policy server element, and stream mixers. There are several ways that these entities can be spread over the available network segments. For example, the ASP and the Regional/Access network can each implement a subset of the entities; for example, the ASP can implement the stream mixing while the rest of the logical entities are implemented in the
- 35 Regional/Access network. Such a division may be feasible from a technical perspective,

5 but the additional exposed interfaces may require standardization or bilateral agreement. There might not be much of a business case for such a model because there is little incentive for either the ASP or Regional/Access network to give up part of the service offering.

10 Furthermore, all of the entities can be implemented in the regional/Access network. This option offers some simplicity from the Regional/Access network provider's perspective because no ASP is involved. This would probably be balanced, however, by the network provider's need to decouple the videoconference service offering from the general DSL networking aspects.

15 Finally, the ASP can implement all of the logical entities while the Regional/Access network provider concentrates on the transport issues. This approach is adopted for the rest of this section -- the ASP handles all of the mixing as well as the application layer control. A reference diagram for the service with three users is shown in **FIG. 23**.

20 From the user's perspective, the videoconferencing service has the following capabilities in accordance with some embodiments of the present invention:

Creation/Activation: the user can interact with the ASP and either request a reserved conference (without pre-designated participants) or activate a previously reserved conference; Termination: the conference ends at a pre-designated time; Adding Participants: All users are designated in advance; Dropping Parties: Although 25 individual parties may stop participation in the conference, the resources in the network supporting their connections remain in place; and/or Stream Mixing: Basic audio and video mixing are provided. Each participant receives all of the other participants' audio and receives video from the participant with the loudest current audio.

30 Assumptions regarding the service are as follows: the ASP that offers the videoconference service will host the MCU; the ASP's MCU will support the ASP's subscribers in all ASP networks for which that ASP is participating; videoconference client software compatible with an ASP's videoconference service is resident on all participant PCs; users that are not subscribed to the ASP's videoconference service will 35 not be supported; DHCP leases do not expire; SIP Application Level Gateway (ALG) functions for handling NAT traversal are provided in the RG; the ASP providing the videoconference service maintains a common address repository or locator for its

5 subscribers. ASP's may be unwilling to share or store their subscriber information in a network database; mechanisms are in place to support application level communication between two ASP networks (see the dotted line shown); the ALG functions in the RG use DiffServ Code Points (DSCP) from the voice and video streams and the port information pushed to it through the ACS profile to map audio and video flows to ports that are known  
10 to the BRAS for reclassification. A simpler approach may be to classify packets coming from the videoconference client based on packet type and protocol ID but that would mean the audio and video RTP streams could not be distinguished by the classifier and would have to share the same priority; the DSCPs used by the videoconference clients are standardized; and/or by its nature RTP is a unidirectional stream, but RTCP is bi-  
15 directional. Each pair of RTP and RTCP UDP streams defines a channel. To simplify the presentation, only one direction of the RTP stream is shown for audio and data and only one control stream is shown. Typical SIP and H.323 videoconference implementations may require additional data and control streams to complete fully bi-directional data flows for all participants.

20 At least two workable business models can support this videoconferencing service. In the simplest model, the videoconference ASP arranges for all potential conference participants to have the necessary policies in place to support the service. Once this infrastructure is provisioned, any subset of the participants can hold a videoconference at any time. A slightly more complex model has some advantages  
25 for demonstration purposes – in this model, the videoconference ASP makes the necessary changes needed in the network to support a particular videoconference (and only the participants for that conference receive upgraded profiles to support their session). This model, which is used in this section, does not require that the policy be in place at all times, but may require a window (perhaps 24 hours) during which the  
30 provisioning changes are made.

A number of billing models are possible. In some embodiments, the ASP bills (flat rate, usage, etc.) videoconference subscribers for their service. The Regional/Access network provider bills the ASP for hosting the service on the ASP network and for the usage of the Regional/Access network. Note that additional  
35 opportunities for the business model are possible for offering centralized billing, authentication, and presence capabilities to videoconference ASPs.

The static provisioning model imposes some restrictions on videoconferencing service models. Reservations are made well in advance to allow the flow-through

5 provisioning to occur before the start of the conference. The reservation window thus needs to close before the start of the conference, for example 24 hours prior. No real-time adjustment of the schedule (such as early teardown because the participants finished early) is possible. The only way to update the participant list is for the user to request a replacement conference before the reservation window closes.

10 Despite the use of the static provisioning model, the ability to map a particular conference's flows to a classifier still makes it possible to offer reasonable service features. The user may be able to set up multiple conference calls with different sets of people and with different QoS and bandwidth requirements (for example, a reduced frame rate may be desired for a conference a day after the conference in this example  
15 because several BRI users will be on the call). Without the mapping between the flows and the classifier, the user may have been able to have only one outstanding conference request. In addition, the user may be able to modify the arrangements for a particular conference (*e.g.*, if the participant roster or start/end times change) provided that the reservation window (24 hour notice) has not closed.

20 A goal of this section is to demonstrate that the Framework and Interface and Data Model are sufficient to support this basic videoconference service. After discussing the individual streams needed for videoconferencing, flows for setting up and tearing down videoconferencing flows in accordance with some embodiments of the present invention are presented. At the end of this section, the network model is  
25 expanded to include the DSL network's entities and further exercise the data model and messages that have been defined.

#### Videoconferencing Scenario Descriptions

The following sequence of events may occur in the process of registering for the ASP videoconference service, reserving a particular conference, and tearing it  
30 down once the conference is over. Assume that three users A, B, and C will be involved in the videoconference and that A will be the originator. For simplicity, the details of the Regional/Access network (DSL Service Manager, UNI and ANI protocol handlers, ACS, BRAS, etc.) are not shown – the expanded flows have been shown in Section 6.4. The step numbers shown in **FIG. 24** and **25** correspond with  
35 the list provided below:

1. Assume that Users A, B, and C already have established PPP sessions between their RG's and the DSL network provider.

- 5        2. On the videoconference ASP website, User A registers to be able to set up  
videoconferences by setting up their user profile, billing options, etc.
3. User A decides to hold a videoconference with Users B and C on Tuesday 3:00-  
4:00 and arranges this with the videoconference ASP.
4. The ASP establishes a service sessions with the Regional/Access network and  
10        is authenticated.
5. The ASP sends application flow control requests to the Regional/Access  
network requesting changes to support the videoconference.
6. The Regional/Access network pushes new application flow policies to the  
BRAS, ACS, and RG's A, B, and C that are specific to the videoconference  
15        application. The videoconference stream facilities are now available.
7. The videoconference starts at 3:00 on Tuesday (note that the flow has now  
moved). Inside the control streams, the videoconference ASP uses SIP to  
establish the necessary conference legs to users A, B, and C. The streams  
from the users are placed appropriately in the queues by the classifiers, are  
20        mixed by the videoconference ASP, and appropriately mixed streams are  
distributed to the participants.
8. At 4:00 on Tuesday, the conference is scheduled to end. The videoconference  
ASP releases its internal resources for the mixers and conference control,  
sends SIP BYE messages through the control stream to clear the SIP dialogs  
25        with the users, and sends a billing record so that the appropriate charging takes  
place.
9. The videoconference ASP establishes a service session with the DSL network  
(if necessary) and is authenticated.
10. The videoconference ASP requests deletion of the application flow control  
30        records that supported the videoconference.

The Regional/Access network deletes the policy for the bandwidth and QoS at the  
BRAS, ACS, and RG's for users A, B, and C. The network has now been returned to  
its default state.

Flow Classification for Video Conferencing



5           The videoconference service may require three streams to carry audio, video, and signaling/control as shown in **FIGS. 24 - 27**. The flows referred to using a "+" sign in **FIG. 27** may be set up dynamically at the VC client and the DSCP may be assigned for the audio and video streams. The ALG/NAT maps of the 10.X.X.X ports to the corresponding IP address and ports for audio and video specified in the ACS  
10   profile based on the DSCP set by the VC client. This may ensure that the RG, BRAS and ASP videoconference MCU maintain consistent port information with regard to the various flows.

          The signaling/control stream is used at the application layer for purposes, such as floor control and other needs, that are transparent to the Regional/Access network  
15   provider. Assume that audio and control packets need to travel with high priority and thus are placed into the Expedited Forwarding queue at the RG. Video packets have medium priority and hence will be placed into the Assured Forwarding queue at the RG. The videoconference service does not cause the user to emit any low priority packets that we are aware of; thus, the RG will not need to place any packets into the  
20   Best Effort queue.

A goal is to demonstrate that it is possible for the ASP to push packet classifier information into the DSL network at conference reservation time so as to configure the DSL network for proper placement of packets from the three streams into the appropriate queues as mentioned above. At the time that a videoconference is  
25   reserved (to occur in this case 3:00-4:00 the next day), the user needs to get a conference identifier/PIN from the videoconference ASP. The user will use this conference identifier to get into the correct conference the next day, and will give the conference id to the other participants for the same purpose. For the purposes of this section, assume that this conference identifier does not need to show up in the data  
30   model because it is strictly between the users and the ASP and somehow transferred transparently to the DSL network provider.

          The ASP needs to set up bandwidth and priority for the three streams (control, video, and audio) that are needed between each user and the ASP using a Create Application Flow Control Request message. One benefit of looking at  
35   videoconference as a service example is to better understand how the various flows would be set up and managed through NATs and firewalls and still have those flows appropriately classified throughout. Many protocols establish connections on well-known ports that spawn data flows on ephemeral ports (*i.e.*, dynamically spawned and

5 assigned to a given multimedia call after the initial handshakes). The problem of firewall and NAT traversal is a complex one due, in part, to the large number of different scenarios and the multitude of different solutions to solve them.

For this example, it is assumed that the RG has an ALG function for the support of SIP. Further it is assumed that there is a "trusted" relationship between the  
10 ASP and the Regional/Access network and the use of DSCP markings of packets can be used as part of the classification process.

Referring to **FIG. 24**, information that is used for setting up and classifying the flows required for a videoconference in accordance with some embodiments of the present invention is illustrated. First, during the initial setup, user A registers all participants and  
15 specifies the start time and end times, *etc.*. The ASP reserves IP addresses for the conference on its platform and updates each participant's RG by issuing a *createAppFlowReq* request to the Regional access network. The BRAS uses the IP addresses specified by ASP<sub>1</sub> for reclassifying traffic to ASP<sub>1</sub> and will use the IP of the RG and the DSCP for reclassifying traffic en route to the videoconference client. The profile  
20 that gets pushed to each participant will contain ASP<sub>1</sub>'s IP addresses for control, audio, and video flows. When the start time for the videoconference approaches, each participant will activate their videoconference client on his or her PC and login to the reserved conference.

Once ASP<sub>1</sub> receives the control message for call setup, it can refer to its table of  
25 reserved addresses to be used for the conference. Capability set negotiation occurs at this time (e.g., could be included in SDP component). The RG's ALG/NAT engine uses the DSCP and information from the ACS profile to determine which port it should assign to the RTP flows from the videoconference client. This may ensure consistency for the port information stored in the BRAS for reclassification. ASP<sub>1</sub>, the BRAS, and the RG should  
30 now know all addresses, priorities and shaping information. The videoconference client's RTP streams can begin pushing audio and video.

#### **10. Example Use Scenario - Gaming**

This section illustrates how the DSL Application Framework can support a gaming  
35 service in accordance with some embodiments of the present invention. Though there are many different models for game play and delivery, this section discusses a particular class of games known as "massively multi-player interactive" games. Such games are characterized by substantial numbers of players (greater than 10 and up to

5 the 1000s) and real time or near real-time interactions. Such games place significant demands on network and game server infrastructures. Other classes of games that are not discussed here include turn based games, single player (turn based or real time interactive), and head to head interactive games. Though each of these classes represents a significant number of games available to users, their network requirements are not nearly as complex as those of multi-player interactive games.

#### Gaming Service Overview

Two basic topologies are used to support network gaming: point to point or client server. In client server topology, the player's workstation communicates with a central game server to which other players are also connected. In the point to point topology, each player communicates directly with each other player. A refinement of the client server topology, the hierarchical client server topology, provides the necessary infrastructure to support true massively multi-player environments. These topologies are depicted in FIG. 28.

In the point to point topology, each gaming workstation must transmit its moves and state change information to each other gaming workstation. In addition, each workstation must maintain a consistent and synchronized image of the game universe for each player. As such the point to point topology requires significant computation power in the end user workstation and typically will not scale to supporting more than a number of users.

25 In both forms of the client server topology, the workstation and game server exchange information that is directly relevant only to a specific player. The client workstation is responsible for such tasks as managing user interactions, rendering, and audio feedback, while the server is responsible for maintaining a consistent view of the game universe and communicating changes to the view to player workstations. The difference between the two topologies is one of segmentation. In the hierarchical topology, a server is only responsible for maintaining the state of a portion of the universe. If a player connected to a particular server is interacting with a portion of the universe outside the scope of their immediate server, that server must coordinate with other servers in the network. This partitioning provides significantly more scalability than a simple client server topology.

In addition to maintaining game universe state at communicating state changes to players, a gaming service may provide other auxiliary functions including the following: Session Management: manages active player lists, supports ability to invite

5 participants to join a game; presence and availability management: supports the  
ability of players to locate and determine if opponents are available for play;  
authentication: verify player identities and validate that players are using correctly  
licensed software on their workstation; interactive chat and bulletin board: provides a  
forum for discussion of gaming topics. Can also be used during game play to allow  
10 for intra-team communication; and/or content downloads: provides software update  
and new game delivery services.

Basic game server functionality and auxiliary functions represent a gaming  
service that may be offered in an ASP model in accordance with some embodiments  
of the present invention. The game server and servers for auxiliary functions are  
15 connected to the ASP network. Client workstations access a game server or auxiliary  
function server through their ASP network connection. From the perspective of the  
DSL network, whether a gaming service implements a client/server or hierarchical  
client/server topology is not important. The DSL network is only involved in the  
transport of traffic between one or more game workstations and the game server to  
20 which they are connected. This service model is show in **FIG. 29**.

#### Traffic and Flow Characterization

In a client/server multiplayer gaming service, the game server and player  
workstation communicate state change and play event information in real time. The  
workstation informs the server of player triggered events including the following:  
25 Player moves; Player takes a shot; Player changes rooms; and/or Player picks up an  
object.

In a real-time game, the server reconciles these play event messages as they  
are received from each workstation or peer server. It then communicates state change  
information to each client workstation. These state change messages contain only  
30 information relevant to the particular player – only information about objects  
currently visible to the player is communicated. Examples of this information  
include: movement of other objects within the player's current view; hits made by the  
player; damage incurred by the player; death of the player or other players; and/or  
communication from the server or other players. Unfortunately, there does not appear  
35 to be a standard protocol for such communications; each gaming system seems to  
define its own methods of communication. The basic characteristics, however, seem  
to be similar.

5           While communication from the workstation to the server is typically event driven, server to workstation communication is often continuous. Servers often send state change messages in frames at a defined rate – 10, 20, 30 frames per second. Frames tend to be significantly larger than voice or video frames. The total time required to send a user event, reconcile its impact on the game universe, and  
10       communicate state change back to the workstation may become the limiting factor in player reaction time. The longer the total time, the less reactive a player can be and the less interactive the gaming experience may become.

          Reconciliation time is driven by server capacity and load. Message delivery times are driven by network limitations. For many games, a total round trip "ping"  
15       time of 200-350ms is considered acceptable while 100ms is considered exceptional. Anything greater than 500ms may become very obvious to the player and is perceived as sluggishness. As latency increases it becomes more likely that players do not share a consistent view of the universe.

          In summary, game play related traffic can be characterized as follows: steady  
20       frame rate; large frame size (relative to voice or video); and/or latency sensitive. Auxiliary services generally do not share these characteristics. They typically are similar or identical to traditional Internet Web based services and do not suffer from significant impacts due to latency.

          The bandwidth requirement for play related traffic is generally lower than for  
25       video services, but the latency sensitivity of game play traffic typically necessitates better than best-effort treatment. Flows related to game play may be placed in an assured forwarding queue at a minimum. Auxiliary services may be handled on a best effort basis. Play related traffic and auxiliary service traffic are typically carried in different flows.

30           Traffic within a game play flow may be further differentiated in accordance with additional embodiments of the present invention. For example, within the context of a particular game certain events may be treated with higher priority than others. This may be supported by allowing the application to use and set multiple diffserv code-points. Such use, however, may only be permitted if there is a trusted  
35       relationship between the ASP gaming host and the transport network.

#### Example Scenario Description

          The call flow for gaming is similar to Turbo button. The game provider needs to negotiate bandwidth profiles between the game server and the player workstation

5 for the purposes of game play traffic. The steps in this scenario are illustrated in  
FIGS. 30 and 31, in accordance with some embodiments of the invention, as follows:

1. Subscriber establishes PPP session between RG and DSL network provider.
2. Subscriber accesses ASP gaming providers web site and registers for game  
play.
- 10 3. ASP gaming provider queries subscriber bandwidth profile and determines  
current profile to be insufficient for game play.
4. ASP creates application bandwidth/QOS profile at Regional Access Network.
5. ASP acknowledges subscription.
6. Regional access network pushes new flow qualifier and bandwidth info for  
15 game service to routing gateway.
7. Subscriber joins game using QOS enabled session.

#### 11. Application Flow Control Data

Some embodiments of the present invention will now be discussed with  
20 respect to Figure 32. As discussed above, a regional/access network 1001 such as a  
digital subscriber line (DSL) network may be used to provide broadband data  
connectivity between one or more network service providers 1003b-c, application  
service providers 1005a-b, and one or more customer premises networks 1007. While  
connectivity between the regional/access network 1001 and a single customer  
25 premises network 1007 is illustrated in Figure 32, it will be understood that the  
regional/access network 1001 generally will support connectivity with many customer  
premises networks.

A network interface device (NID) 1009 may provide an interface between  
local loop wires of the regional/access network (RAN) 1001 and the customer  
30 premises network 1007. On the customer side of the NID 1009, a routing gateway  
1011 (such as a DSL modem remote from the regional/access network 1001) may  
receive data from and transmit data to the regional/access network 1001. Moreover,  
multiple user devices 1015a-b (such as personal and/or laptop computers) may  
concurrently access the regional/access network 1001 through the routing gateway  
35 1011. More particularly, the NID 1009 may provide an interface between the routing  
gateway 1011 and a local loop providing voice and data connectivity to a main  
distribution frame (MDF) 1019 of a public switched telephone network (PSTN) so  
that data connectivity is provided as a digital subscriber line. It will be understood

5 that the operator of the regional/access network **1001** may also provide telephone voice and/or other data services. Telephone voice and/or other data services are not discussed herein or illustrated in Figure 32 for the sake of clarity.

The access node **1021** may provide aggregation between an access portion of the network and a regional portion of the network, and may provide aggregation of  
10 data from multiple digital subscriber lines. The automated configuration server (ACS) **1023** may provide configuration information to routing gateways **1011** at the various customer premises networks **1007**, and the UNI protocol handler **1024** may provide an interface between the service manager **1043** and the automated configuration server **1023**. The regional/access network **1001** may also support  
15 legacy asynchronous transfer mode (ATM) network service providers (NSP) **1003a** using one or more ATM transceiver(s) **1025** and/or ATM switches **1027**.

A concentrator **1029** such as a broadband remote access server (BRAS) may provide aggregation between the regional/access network **1001** and network service providers **1003b-c** and application service providers **1005a-b**. The concentrator **1029**  
20 and the routing gateway **1011** may provide control of session bandwidth and queuing priority for data transmitted by and received from the particular routing gateway **1011**. Moreover, the application flow control information for each session being conducted at a routing gateway **1011** may be stored at that routing gateway **1011**. Accordingly, the concentrator **1029** and the routing gateway **1011** may implement  
25 appropriate bandwidth restrictions and/or queuing priorities for all data sessions being conducted between the two. As further shown in Figure 32, data from the network service providers **1003b-c** and application service providers **1005a-b** may be transported through an IP network **1033** to the RG **1011** via the RAN **1001**, and the IP network **1033** may also transport data from the RAN **1001** to the network service  
30 providers **1003b-c** and the application service providers **1005a-b**.

In addition, an application framework infrastructure **1041** provides data flow management for data sessions between routing gateways **1011** and network service providers **1003b-c** and application service providers **1005a-b** according to  
embodiments of the present invention. More particularly, a service manager **1043**  
35 (such as a DSL service manager) may coordinate implementation of data flow characteristics for particular sessions between network service providers (NSPs), application service providers (ASPs), and routing gateways. As shown in Figure 32, communications between the service manager **1043** and application service providers

5    **1005a-b** may be provided by an application-to-network interface (ANI) protocol handler **1045**. Communications between the service manager **1043** and network service providers **1003b-c** may be provided by network-to-network interface (NNI) protocol handler **1047**. Communications between the service manager **1043** and the concentrator **1029** may be provided through the concentrator adapter **1049**.  
10    Communication between the service manager **1043** and the routing gateway **1011** may be provided through the UNI protocol handler **1024**, the automated configuration server **1023**, the IP network **1033**, the concentrator **1029**, ATM switch **1027**, access node **1021**, MDF **1019**, and network interface device **1009**.

As shown in Figure 32, the application framework infrastructure **1041** may  
15    include ANI protocol handler **1045**, NNI protocol handler **1047**, concentrator adapter **1049**, UNI protocol handler **1024**, automated configuration server **1023**, service manager **1043**, session data store **1051**, and provisioning interface **1053**. As illustrated in Figure 32, functionality of the application framework infrastructure **1041** may be implemented outside functional elements illustrated in the regional/access  
20    network **1001**. In an alternative, functionality of some or all of the elements of the application framework infrastructure **1041** may be implemented within one or more elements illustrated in the regional/access network **1001**. For example, some or all of the elements of the application framework infrastructure **1041** may be implemented within the concentrator **1029**. More particularly, some or all of the elements of the  
25    application framework infrastructure **1041** may be implemented as software components operating on a server providing functionality of the concentrator **1029**. In addition or in an alternative, elements of the application framework infrastructure **1041** may be implemented as software components operating in elements of the regional/access network **1001** other than the concentrator **1029**, and/or operating in an  
30    additional element or elements (such as one or more additional servers) not included in the regional/access network **1001** illustrated in Figure 32.

According to embodiments of the present invention, the regional access network **1001** may provide a data path for traffic flow between one or more routing gateways **1011** and one or more of legacy ATM **1003a**, NSP's **1003b-c**, and/or ASPs  
35    **1005a-b**. More particularly, a data path may be provided through IP network **1033**, concentrator **1029**, ATM **1027**, access node **1021**, and MDF **1019**. Elements of the regional/access network **1001** and/or the application framework infrastructure **1041** may also provide separate signaling paths. A signaling path between service manager



5    **1043** and one or both of ASPs **1005a-b** may be provided through the ANI protocol handler **1045**, and IP network **1033**. A signaling path between service manager **1043** and NSP **1003b** and/or NSP **1003c** may be provided through NNI protocol handler **1047**, concentrator **1029**, and IP network **1033**. A signaling path between the service manager **1043** and concentrator **1029** may be provided through concentrator adapter  
10    **1049** and IP network **1033**. A signaling path between the service manager **1043** and the routing gateway may be provided through UNI protocol handler **1024**, automated configuration server **1023**, concentrator **1029**, ATM **1027**, access node **1021**, and MDF **1019**.

More particularly, the concentrator **1029** may be a broadband remote access  
15    server (BRAS), and a particular concentrator adapter **1049** may be used to provide an appropriate interface for a particular broadband remote access server. For example, the concentrator **1029** may be provided using a broadband remote access server such as a Shasta 5000 Broadband Service Node produced by Nortel Networks or a Juniper ERX-310 BRAS/edge router produced by Juniper Networks. Accordingly, the  
20    concentration adapter **1049** may be modified to provide compatibility with different concentrators.

While not separately illustrated in FIG. 32, each of the routing gateway **1011**, the application service providers **1005a-b**, and the network service providers **1003b-c** may include a transceiver(s) to transmit data to and receive data from the  
25    regional/access network **1001**. In addition, the concentrator **1029** may also include a transceiver to transmit data to and receive data from the application service providers **1005a-b** and the network service providers **1003b-c**. Similarly, the MDF **1019** and/or the access node **1021** may include a transceiver to transmit data to and/or receive data from routing gateways.

30    Moreover, transmitters, receivers, and/or transceivers according to embodiments of the present invention may be wired and/or wireless. By way of example, transmitters, receivers, and/or transceivers according to embodiments of the present invention may be provided using circuit-switched networks, and/or packet-based networks and/or network elements, such as Internet Protocol (IP) networks and  
35    elements. In addition or in alternatives, transmitters, receivers, and/or transceivers according to embodiments of the present invention may be provided wirelessly, for example, using cellular communications, personal communications systems (PCS), WiFi, Ultrawideband, Bluetooth, and/or satellite communications. In addition or in

5 other alternatives, transmitters, receivers, and/or transceivers according to  
embodiments of the present invention may be provided in wireline environments such  
as in cable communications and/or power line communications.

Information relating to data flow characteristics can be stored in the session  
data store **1051**, and a provisioning interface **1053** may allow an operator of the  
10 regional/access network **1001** to provision bandwidth and Quality-of-Service settings  
for each individual subscriber. Accordingly, application flow control information for  
each session conducted at each routing gateway may be stored at the session data  
store **1051**, and at the routing gateway **1011**. Moreover, an application flow control  
record may be created by the service manager **1043** responsive to a request from one  
15 of the application service providers **1005a-b** when a data session with a routing  
gateway is established with one of the application service providers, and the  
application flow control record may be deleted by the service manager **1043**  
responsive to a request from one of the application service providers **1005a-b** when  
the data session with the routing gateway is terminated. Operations of elements  
20 illustrated in Figure 32 are discussed above in greater detail, for example, with respect  
to Figures 1-7 and 13-21, and/or at Sections 6.4, 6.4.1, and 6.4.2, and more  
particularly, at Section 6.4.2 "Application Flow Control Record Creation Scenario  
Messaging Flow", and at Section 6.4.2 "Application Flow Control Record Deletion  
Scenario Messaging Flow".

25 According to particular embodiments of the present invention, a user at a user  
device **1015a** may establish a data session using an application service provided by  
one of the application service providers **1005a-b** over a data path established through  
the routing gateway **1011**, the network interface device **1009**, and the regional/access  
network **1001**. For example, the application service provider **1005a** may provide one  
30 or more of application services such as gaming, video on demand, and/or access to  
virtual private networks (VPNs) via IPsec and/or another Internet Protocol tunneling  
technique. The application service provider **1005a** may initiate establishing a data  
session through the regional/access network **1001** and the routing gateway **1011**  
responsive to a request received from the user device **1015a** over the regional/access  
35 network **1001**. When the data session is complete and/or when a termination request  
is received from the user device **1015a**, the application service provider **1005a** may  
initiate terminating the data session.

5           More particularly, the application service provider **1005a** may initiate a data session with a user device through a particular routing gateway **1011** by generating an application flow control record request (such as an AppFlowControlRequest as discussed above). The application flow control record request may include an identification of the service provider (such as a SP\_ID as discussed above), an  
10   identification of the routing gateway (such as a DSL\_Line\_ID discussed above), and data flow characteristics for the application service being requested (such as a Flow\_Classifier, a Flow\_Priority, and a Flow\_Bandwidth discussed above). The application flow control record request may also include an authorization code (previously provided by the regional/access network **1001**) that identifies the  
15   particular application service being established.

          The application flow control record request can be received at the ANI protocol handler **1045** and forwarded to the service manager **1043**. If an authorization code is included in the request, the service manager **1043** may validate the application flow control record request using the authorization code, and create an application  
20   flow control record for the data session if the request is valid. In an alternative, the application flow control record may be created without requiring validation. More particularly, the application flow control record may be created by saving information from the application flow control record request at the session data store **1051**.

          The application flow control record may include the data flow characteristics  
25   for the application data session, and the data flow control characteristics may include a bandwidth characterization (such as a Flow\_Priority as discussed above) for the application service and a priority characterization (such as a Flow\_Priority as discussed above) for the application service. The service manager **1043** may communicate the data flow characteristics for the application service and requesting  
30   routing gateway **1011** through the regional/access network **1001**. For example, the service manager **1043** may communicate the data flow characteristics for the application service through the concentration adapter **1049** and the IP network **1033** to the concentrator **1029**. The service manager **1043** may communicate the data flow characteristics for the application service to the routing gateway **1011** through the  
35   UNI protocol handler **1024**, the automated configuration server **1023**, the IP network **1033**, the concentrator **1029**, the ATM **1027**, the access node **1021**, and the MDF **1019**. Accordingly, the data flow characteristics for the routing gateway **1011**

5 requesting the application service may be stored at the session data store 1051 and at the requesting routing gateway 1011.

The data flow characteristics for the session of the routing gateway 1011 using the application service provided by the application service provider 1005a may thus be saved as an application flow control record for the routing gateway 1011 at the  
10 session data store 1051 used by the service manager 1043. Moreover, the data flow characteristics can be forwarded to and saved at the routing gateway 1011.

Accordingly, the data flow characteristics can be used at the concentrator 1029 and at the routing gateway 1011 when providing the data path between the routing gateway 1011 and the application service provider 1005a to support a session of the routing  
15 gateway 1011 using the application service provided by the application service provider 1005a. More particularly, the data flow characteristics can be used by the concentrator 1029 and the routing gateway 1011 to police the flow of data of the session between the routing gateway 1011 and the application service provider 1005a according to the data flow characteristics provided by the application service provider  
20 for the session.

When the session between the application service provider 1005a and the routing gateway 1011 is over, the data flow characteristics saved at the session data store 1051 may be deleted. For example, the application service provider 1005a may determine that the session with the routing gateway 1011 is complete responsive to  
25 receiving a termination request from the routing gateway 1011, responsive to determining that a time out period has passed without communication from the routing gateway 1011, and/or responsive to determining that a session time limit has been exceeded.

Once the application service provider 1005a determines that the session is  
30 complete, the application service provider 1005a may transmit a request to delete the data flow characteristics for the session, and the request may be received by the ANI protocol handler 1045 and passed to the service manager 1043. The service manager 1043 may then delete the data flow characteristics saved at the session data store 1051 for the session of the routing gateway 1011 using the application service provided by  
35 the application service provider 1005a, and the data path between the routing gateway 1011 and the application service provider 1005a may be terminated to end the session of the routing gateway using the application service provider.

5           A data network may be operated between a routing gateway for a subscriber and an application service provider according to additional embodiments of the present invention illustrated in Figure 33. In particular, the data network may receive an identification of the routing gateway, an identification of the application service provider, and data flow characteristics of an application service for a session of the  
10   routing gateway using the application service provided by the application service provider at block **2001**. Responsive to receiving the information, the data flow characteristics of the application service may be saved at block **2003**, and the data flow characteristics may be forwarded to the routing gateway at block **2005**. More particularly, the data flow characteristics may include a bandwidth characterization  
15   and a priority characterization for the application service.

          In addition, an authorization code may be received with the identification of the routing gateway, the identification of the application, and the data flow characteristics, and the authorization code may be validated at the network before saving the data flow characteristics. Moreover, saving the data flow control  
20   characteristics may include creating an application flow control record for the routing gateway, and the data flow characteristics may be at first and second databases within the data network. Moreover, the first database may be associated with a concentrator of the data network, and the second database may be associated with a service manager of the data network.

25           Receiving identifications and data flow characteristics at block **2001** may be preceded by receiving a request from a routing gateway for a session using the application service provided by the application service provider, and forwarding the request from the routing gateway to the application service provider. Once the data flow characteristics have been saved at the data network and forwarded to the routing  
30   gateway at blocks **2003** and **2005**, an interconnection may be provided between the routing gateway and the application service provider in accordance with the data flow characteristics to support a session of the routing gateway of the subscriber using the application service provided by the application service provider.

          Once the data session between the routing gateway and the application service  
35   provider is complete so that the data path is no longer needed, the data flow characteristics saved at the data network for the session may be deleted, and the data path between the routing gateway and the application may be terminated. More particularly, a request may be received from the application service provider to delete

5 the data flow characteristics before deleting the data flow characteristics, and the data flow characteristics may be deleted responsive to the request from the application service provider to thereby terminate the data path and the data session. Operations relating to application flow control records are also discussed above with respect to Figures 17 and 18.

10 An application service provider may be operated to provide an application service over a data network to a routing gateway for a subscriber according to still additional embodiments of the present invention illustrated in Figure 34. As shown at block 3001 of Figure 34, the application service provider may transmit to the data network an identification of the routing gateway, an identification of the application  
15 service provider, and data flow characteristics of the application service for a session with the routing gateway using the application service. At block 3003, the application service may be provided over the data network and routing gateway in accordance with the data flow characteristics transmitted to the data network to support a data session of the application service provider with the routing gateway.

20 More particularly, the routing gateway may be coupled to the data network via a digital subscriber line, and the identification of the routing gateway may be a digital subscriber line identification. Moreover, the data flow characteristics of the application service may include a bandwidth characterization for the application service and a priority characterization for the application service. In addition,  
25 transmitting at block 3001 may also include transmitting an authorization code for the application service, and the application service provider may wait to receive a validation of the authorization code from the data network before providing the application service at block 3001.

Transmitting at block 3001 may be performed responsive to receiving a  
30 request from the routing gateway for a session using the application service. When the data session providing the application service to the routing gateway is complete, the application service provider may transmit a request to the application service provider to delete the data flow characteristics for the session of the routing gateway using the application service, and the application service over the data network and  
35 routing gateway may be terminated. The data session may be terminated, for example, responsive to a request from the routing gateway, responsive to passing of a predetermined period of time without activity, and/or responsive to passing of a predetermined period of time allowed for a data session.

5           A routing gateway may be operated to provide subscriber use of an application  
service provided by an application service provider over a data network according to  
yet additional embodiments of the present invention illustrated in Figure 35. In  
particular, the routing gateway may receive data flow characteristics of the application  
service for a session of the routing gateway using the application service provided by  
10   the application service provider at block 4001. At block 4003, access to the  
application service may be provided over the data network in accordance with the  
data flow characteristics received from the data network to support a data session with  
the application service provider.

          More particularly, the routing gateway may be coupled to the data network via  
15   a digital subscriber line. Moreover, the data flow characteristics of the application  
service may include a bandwidth characterization for the application service and a  
priority characterization for the application service. In addition, receiving the data  
flow characteristics at block 4001 may be preceded by transmitting a request to the  
application service provider for a session using the application service provided by the  
20   application service provider.

          Many variations and modifications can be made to the preferred embodiments  
without substantially departing from the principles of the present invention. All such  
variations and modifications are intended to be included herein within the scope of the  
present invention, as set forth in the following claims.

25